

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3674)

Set Hemlock post, 3 ft. long, 3" sq., 24" in the ground for $\frac{1}{4}$ Sec. cor. mkd. $\frac{1}{4}$ S on W. face, from which
A Hemlock 10" dia., bears N.80°E., 31 lks. dist., mkd. $\frac{1}{4}$ S BT.
A Hemlock 10" dia., bears S.70°W., 12 lks. dist., mkd. $\frac{1}{4}$ S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11547)

Point for the original $\frac{1}{4}$ sec. cor. determined by reference to the record measurements from both old bearing trees. At point for corner, set an iron post, 3 ft. long, 1" dia., 28" in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S14|S13
1943 from which

A dead Hemlock 22" dia., bears N.76 $\frac{1}{4}$ °E., 31 lks. dist., mkd. $\frac{1}{4}$ S BT. (Old BT)
A Hemlock 11" dia., bears S.83°W., 12 lks. dist., mkd. $\frac{1}{4}$ S BT. (Old BT.)
A Fir 36" dia., bears S.59°E., 56 lks. dist., mkd. $\frac{1}{4}$ S13 BT. (New BT)
A Fir 48" dia., bears N.77°W., 25 lks. dist., mkd. $\frac{1}{4}$ S14 BT. (New BT)

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June/July 1966 - C.S. File 54/27-16

Found - 1943 GLO brass cap mkd.
Orig. 22" Hemlock rotted & burned, N.76 $\frac{1}{4}$ °E., 20.5 ft., no scribe found.
Orig. 11" Hemlock S.83°W., 7.9 ft., down & burned, no scribe.
1943, 36" Fir, now stump S.59°E., 37.0 ft. shows "T" scribe.
1943, 48" Fir, now burned & shattered snag, N.77°W., 16.5 ft., shows " $\frac{1}{4}$ S14 BT" scribe in poor condition.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs - 4" D.Fir S.76°W., 12.6 ft. mkd. ¼ S13 CS BT.
8" Hemlock S.88½°E., 61.0 ft. mkd. ¼ S13 CS BT.
Brass cap lies on west side of 30" log, 60 ft. west of cutting line, course N & S, in heavy reproduction. Also has steel fence post alongside brass cap.

Tony Hostetter - For: Roseburg Resources Co. - May 2000 - C.S. File 65/30-9

Found - 1943 GLO brass cap & accessories described by Douglas County Surveyor in 1966, except for the following:
36" Fir stump @ S.59°E., is in place but scribing is gone.
48" Fir snag @ N.77°W., is in place, scribing gone, BLM tag.
8" Hemlock @ S.88½°E., is now 18" with scribing visible.
4" Fir @ S.76°W., is now 10" w/face evident & BLM tag.
New BTs - 12" Hemlock, faced & scribed "S13 ¼ BT", BT tag, bears: S.5°E., 5.7 ft. to 6" spike placed in root collar.
10" Fir, faced & scribed "S14 ¼ BT" BT tag, bears: N.5°W., 5.1 ft. to 6" spike in root collar.

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22426)

The ¼ sec. cor. of secs. 13 and 14, perpetuated by the Douglas County Surveyor's Office in 1966, subsequently perpetuated by Hostetter, in 2000, monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. Price
A sawed, decayed fir stump, 36" dia., bears S.59°E., 37.0 ft., with no marks visible.
A burnt, decayed fir stump, 61" dia., bears N.77°W., 16.5 ft., with no marks visible.
and the remains of bearing trees mkd. by the Douglas County Surveyor's Office
A hemlock, 17" dia., bears S.87¾°E., 60.7 ft., with scribe marks S13 BT visible on a partially healed blaze.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A roothole bears S.71 $\frac{3}{4}$ °W., 12.4 ft., downhill from which is an uprooted, sawed fir stump, 12" dia., with no marks visible.
and the remains of bearing trees mkd. by Hostetter
A hemlock snag, 13" dia., bears S.3 $\frac{1}{2}$ °E., 6.4 ft., with fragmentary scribe marks visible on a partially healed blaze.
A fir, 12" dia., bears N.6 $\frac{1}{2}$ °W., 6.1 ft., with fragmentary scribe marks visible on a partially healed blaze.
and a new bearing tree
A hemlock, 9" dia., bears N.70 $\frac{1}{4}$ °E., 22.3 ft. mkd. $\frac{1}{4}$ S13 BT Corner is located on a SW. slope.