

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3674)

Set cedar post, 4 ft. long, 4" sq., 24 in the ground for cor. to secs. 11, 12, 13, & 14, mkd. T25S S12 on NE., R3W S13 on SE., S14 on SW., and S11 on NW. faces, with 4 notches on S. and 1 notch on E. edges, from which

A Fir 36" dia., bears N.85°E., 40 lks. dist., mkd. T25S R3W S12 BT.

A Cedar 18" dia., bears S.76°E., 23 lks. dist., mkd. T25S R3W S13 BT.

A Fir 72 dia., bears N.40°W., 18 lks. dist., mkd. T25S R3W S11 BT.

A Hemlock 12" dia., bears S.50°W., 18 lks. dist., mkd. T25S R3W S14 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11547-48)

Point for original cor. of secs. 11, 12, 13, and 14, determined by reference to the record measurements from all the old bearing trees. At point for corner set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd.

T25S R3W

S11|S12

S14|S13

1943

from which

A Fir 36" dia., bears N.86½°E., 40 lks. dist., with partial scribe marks on face of old bark blaze. (Old BT)

A Red Cedar 20" dia., bears S.68¼°E., 23 lks. dist., mkd. S13 T25S R3W BT. (Old BT)

A Hemlock 24" dia., bears S.53°W., 18 lks. dist., mkd. S14 T25S R3W. (Old BT)

A Fir 50" dia., bears N.38½°W., 18 lks. dist., with blaze healed. (Old BT)

A Hemlock 10" dia., bears N.76 3/4°E., 16 lks. dist., mkd. T25S R3W S12 BT. (New BT)

Doug. County Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - July/Aug. 1966 - C.S. File 54/27-53

Found - GLO brass cap mkd. 1943, with steel fence post alongside.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Orig. 36" now 40" Fir N.86½°E., 26.4 ft., shows visible bark scribe "S12". Alive.
Orig. 20" now 23" R.Cedar S.68¼°E., 15.2 ft., badly burned. Alive.
Orig. 24" now 30" Hemlock S.53°W., 11.9 ft. Previously opened. Scribe visible.
Orig NW BT, now stump. 1943 BT to NE, down & rotted
New BTs- 30" Hemlock S.53°W., 11.9 ft. rescribed "T25S R3W S14 CS BT".
6" D.Fir N.53°W., 20.8 ft. mkd. T25S R3W S11 CS BT.
17" R.Cedar S.41°E., 49.1 ft. mkd. T25S R3W S13 CS BT.
10" Hemlock N.16°E., 15.5 ft. mkd. T25S R3W S12 CSBT
Corner lies on very steep NW slope.

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22426-7)

The cor. of secs. 11, 12, 13, and 14, perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed fir stump, 47" dia., bears N.86½°E., 26.4 ft., with no marks visible.
A cedar, 31" dia., bears S.68¼°E., 15.2 ft., with no marks visible on a hollow, burnt blaze.
A sawed hemlock stump, 37" dia., bears S.53°W., 11.9 ft., with fragmentary scribe marks visible on an open blaze.
A sawed, decayed fir stump, 52" dia., bears N.38¼°W., 11.9 ft., with a healed blaze.
and the remains of bearing trees mkd. by the Douglas County Surveyor's Office
A hemlock, 24" dia., bears N.13¾°E., 14.9 ft., with a healed blaze.
A sawed, decayed cedar stump, 28" dia., bears S.41½°E., 48.0 ft., with a healed blaze.
A hemlock, 10" dia., bears N.54¼°W., 21.0 ft., with a healed blaze.
and a bearing tree mkd. by person(s) unknown
A hemlock, 12" dia., bears S.53°E., 24.4 ft., with fragmentary scribe marks visible on a partially healed blaze, and a brass washer, mkd. 2354, driven in blaze.
and a new bearing tree

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 5" dia. bears S.89°W., 16.8 ft mkd. T25S R3W S14 BT
Raise a mound of stone, 2½ ft dia. 2 ft high, around iron post
Corner is located on a steep, N. slope.