

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36 of T24-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under Contract #152 dated June 3, 1871
(DCSO records, Volume 7 Page 2946)

Set post cor. to secs. 1, 2, 35 and 36, from which
A Fir 30" dia., bears N.55°E., 41 lks. dist.
A Fir 30" dia., bears S.75°E., 15 lks. dist.
A Fir 48" dia., bears S.62°W., 58 lks. dist.
A Fir 40" dia., bears N.72°W., 17 lks. ditst.

Found and used by Laban Wheeler, under Contract #467
dated April 7, 1883 (DCSO records, Vol. 7 Page 2970)

GLO Dependent Resurvey by Norman D. Price under Special
Instructions dated April 5, 1940 (DCSO records, Volume 27
page 11538)

Point for original cor. of secs. 1, 2, 35 and 36, determined
by reference to the record distance from each of the old
bearing trees.

At point for corner, set an iron post, 3 ft. long 2" dia., 28"
in the ground with brass cap mkd.

T24S R3W

S35|S36

S2|S1

T25S

1944

from which

A fir 40" dia., bears N.53°E., 41 lks. dist., mkd. on
bark T24S R3W S36 BT. I reblaze & remark this old
bearing tree T24S R3W S36 BT.

A Fir 42" dia. bears S.77°E., 15 lks. dist., with no
scribe marks remaining on badly weathered face of
old bark blaze. I reblaze & remark this old bearing
tree T25S R3W S1 BT.

A Fir 58" dia., bears S.64°W., 58 lks. dist., with no
scribe marks remaining on badly weathered face of
old bark blaze. I reblaze and remark this old BT
T25S R3W S2 BT.

A Fir stump 40" dia. bears N.70°W., 17 lks. dist., with
no scribe marks remaining on badly weathered face of
old bark blaze. (Old BT)

A Hemlock 10" dia., bears N.39½°E., 58 lks. dist., mkd.
T24S R3W S36 BT. (New BT)

A Hemlock 12" dia., bears N.10°W., 4 lks. dist., mkd.
T24S R3W S35 BT. (New BT)