

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3669)

Set Dogwood post, 3 ft. long, 3" sq., 24" in the ground for gr. sec. cor. mkd. $\frac{1}{4}$ S on N. face, from which

A Fir 10" dia., bears N.35°E., 33 lks. dist., mkd. $\frac{1}{4}$ S BT.

A Hemlock 12" diam., bears S.20°E., 9 lks. dist., mkd. $\frac{1}{4}$ S BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Page 11541)

Proportional measurement. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for $\frac{1}{4}$ sec. cor. with brass cap mkd.

$\frac{1}{4}$ S 25

S36
1943

from which

A Fir 16" dia., bears N.21°W., 76 lks. dist., mkd. $\frac{1}{4}$ S 25 BT.

A Fir 11" dia., bears S.47°W., 25 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

Fd. Ok by D.Edwards, 4/1998 - M128-61