

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22425)

The ¼ sec. cor. of secs. 13 and 24, perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed fir snag, 45" dia., bears N.11¼°E., 24.4 ft., with no marks visible.

A roothole bears S.11°E., 28.4 ft.

and a bearing tree mkd. by Price

A fir, 59" dia., bears N.32°E., 77.9 ft., with a healed blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

A sawed fir stump, 21" dia., bears S.31°E., 53.1 ft., with a healed blaze.

A maple, 18" dia., bears N.32¼°W., 8.6 ft., with a healed double blaze.

and a new bearing tree

A fir, 5" dia., bears S.33¼°W., 49.1 ft., mkd. ¼ S24 BT. Corner is located on broken S. slope.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Station (CORS) "DODSON BUTTE CORS ARP", and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", are as follows:
Latitude: 43°23'20.31"N. Longitude: 122°59'57.53"W.