

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Section Corner for 25 & 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records, Volume 9 Page 3585-6 & 3669)

Set Hemlock post 4 ft. long 4" sq., 24" in the ground for corner to secs. 25, 30,31 and 36 marked T25S S30 on NE., R2W S31 on SE., R3W S36 on SW., S25 on NW faces with 5 notches on N and 1 notch on S edges, from which

A Fir 60" dia. bears N.30°E., 44 lks. dist., marked T25S R2W S30 BT.

A Yew 12" dia. bears S.35°E., 33 lks. dist., marked T25S R2W S31 BT.

A Fir 36" dia. bears S.51°W., 50 lks. dist. marked T25S R3W S36 BT.

A Cedar 10" dia. bears N.61°W., 44 lks. dist. marked T25S R3W S25 BT.

GLO Survey of Exterior boundaries of T25-2 by Hezikiah H. Johnson, under Contract #721 dated May 1, 1900 (DCSO records Volume 9 Page 3657-8)

(In the survey of T25S R2W where closing corners were set on exterior lines, the marks on all old section corners were destroyed which referred to the sections bounded by the closing lines)

The cor. of secs. 25 and 36, which is a post 4" sq. from which
A Fir 8" dia. bears N.69°E., 27 lks dist. marked T25S R2W S30 BT.

A Fir 10" dia. bears S.66°E., 41 lks. dist., marked T25S R2W S31 BT.

A Fir 12" dia. bears S.49°W., 58 lks. dist. marked T25S R3W S36 BT.

A Fir 14" dia. bears N.62°W., 31 lks. dist. marked T25S R3W S25 BT.

H.L. Eppstein, Co. Surveyor Wit: N.E. Richardson; Larkin Rice January 1929 - "Old" Corner Renewal book Vol. 1 Page 50

Set corner from Fir tree, scribe marks plain for the S. & E., rest burned out. This tree was probably old tree in Sec. 30 The other trees were all down but evidence of cut marks on same but no scribe mark. I set a Yew wood post for corners and marked:

A 10" Fir S.80°W., 5.5 ft.

A 6" Fir N.15°W., 15.0 ft.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GL0 Dependent Resurvey by Norman D.Price under Special Instructions dated April 5, 1940 (DCS0 records, Volume 27 Page 11510)

 Note: After careful investigation, it is developed that Johnson's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T25S R2W and is therefore rejected as a suitable basis for restoration of lost corners referring to T25S R3W" (From Volume 27 Pg. 11509)

The original sec. cor. which now refers to secs. 25 and 36 only, a basalt stone, 10x8x8 ins. firmly set in a small ring of stone, mkd. with 5 chaining pin scratches on N. and one chaining pin scratch on S. face. At point for corner, set an iron post, 3 ft. long, 2" dia. 28" in the ground, with the original stone deposited at the base, for cor. of secs. 25 and 36, with brass cap mkd.

T25S	T25S
S25	R2W
S36	S30
R3W	

1943 from which

- A D.Fir 14" dia. bears N.69°E., 27 lks. dist., on which I uncover and efface the inscription T25S R2W S30 BT which i find beneath 60 years overgrowth. (A Wheeler BT)
- A hemlock 14" dia. bears S.67½°E., 41 lks. dist., on which I uncover and efface the inscription T25S R2W S31 BT which I find beneath 60 years overgrowth. (A Wheeler BT)
- A Hemlock 12" dia. bears S.51½°W., 58 lks. dist., on which I uncover the scribe marks BT beneath 60 years overgrowth. (A Wheeler BT)
- A Hemlock 24" dia. bears N.61¼°W., 31 lks. dis., with old blaze healed. (A Wheeler BT)
- A Red Cedar 30" dia. bears S.43°W., 86 lks. dist. mkd. T25S R3W S36 BT. (New BT)
- A White Fir 12" dia. bears N.39°W., 48 lks. dist., mkd. T25S R3W S25 BT. (New BT)

Douglas Co. Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June 1966 - C.S. File 54/27-173

 (Cont. Next Page)

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Found - 1943 G10 brass cap.
Orig. 24" Hemlock N.61¼°W., 20.5 ft., alive, shows scar.
Other orig. BTs are now snags or gone.
30" now 32" R.Cedar S.43°W., 56.8 ft., scribe visible on unhealed blaze. Tree alive & in good condition.
12" now 16" W.Fir snag, N.39°W., 31.7 ft. shows good scar.
No trace of BTs recorded by Eppstein.
New BT - 6" yew N.41°W., 25.4 ft. mkd. T25S R3W S25 CS BT.
This corner lies 50 ft. north of Rock Creek Road, course E-W.

BLM Dependent Resurvey by Berry; Wofford; Popken and Glenn S. Baughman under Contract #52500-CT5-1116 Under special instructions dated June 1972. Survey July 1972-Oct. 1975 (DCSO records, Volume 36 Pages 15111-12)

The cor. of secs. 25 and 36 only, monumented with an iron post 2" dia. firmly set, protruding 8" above ground with brass cap. from which the remains of the original bearing trees:
A decayed fir snag 14" dia. bears N.69°E., 27 lks. dist., no marks visible.
A decayed Hemlock stump 16" dia. bears S.67½°E., 41 lks. dist., no marks visible.
A root hole bears S.51½°W., 58 lks. dist., with a down hemlock alongside 16" dia., no marks visible.
A root hole bears N.61¼°W., 31 lks. dist. with a down hemlock alongside, 30" dia., no marks visible.
and the remains of bearing trees mkd. by Price:
A Red Cedar snag 34" dia. bears S.43°W., 86 lks. dist. with scribe marks T25S R3W S36 BT visible on open blaze.
A W.Fir snag 14" dia. bears N.39°W., 48 lks. dist., with healed blaze.
and a bearing tree mkd. by the County Surveyor:
A Yew 6" dia. bears N.41°W., 38 lks. dist., with scribe marks visible on open double blaze.
and a new bearing tree
A Hemlock 15" dia. bears S.55°W., 87 lks. dist., mkd. T25S R3W S36 BT.

Fd. Ok by D. Edwards, 4/1998 - M128-61

continued next page

PRIMARY CORNER DESCRIPTION Section Corner for 25 & 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23036-7)

The cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree
A decayed hemlock stump, size indeterminate, bears S.67½°E., 27.1 ft., with no marks visible.

and remains of the bearing trees mkd. by Price in 1943-44

A cedar snag, 30" dia., bears S.43°W., 56.8 ft., with scribe marks 25S R3W S36 visible on a partially healed blaze.

A root wad, size indeterminate, bears N.39°W., 31.7 ft. with no marks visible.

and remains of a BT mkd. by the Douglas Co Surveyor's Office in 1966

A yew snag, 6" dia., bears N.41°W., 25.1 ft., with scribe marks T25S R3W visible on a partially healed blaze.

and BT mkd. by Berry, Wofford, Popken, & Baughman in 1972-75

A white fir, 24" dia., bears S.57¼°W., 57.4 ft. with a healed blaze. (Record, hemlock, S.55°W.)

and a new bearing tree

A hemlock, 16" dia., bears N.14¼°W., 13.9 ft., mkd. T25S R3W S25 BT. Drive a 2½"x¼" magnetic nail (Mag Nail) at the base on right side center.

The geographic position in NAD 1983 (2011) of this cor., as determined by a tie from a temporary Geographic Position System (GPS) control point, established utilizing dual frequency, carrier phase GPS receivers, relative to "DODSON BUTTE CORS ARP", "CAPE BLANCO CORS ARP", and "ROSEBURG COOP CORS ARP", is as follows:

Latitude: 43°21'34.81"N. Longitude: 122°59'25.55"W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/22/2022 (Filed 4/18/2022) - C.S. File 67/52-22

Found - 2½" GLO brass cap on 1½" ID Iron pipe (properly mkd) projecting 3"

Burnt yew roots N.41°W., 25.1 ft

All other BTs destroyed by fire, then area shovel logged for Power line R/W clearing.

New - 5/8"x30" I.Rod with DCSO plastic cap S.2°W., 43.0 ft, projecting 6".

5/8"x30" I.Rod with DCSO plastic cap S.73°W., 38.8 ft, projecting 6".

Continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Section Corner for 25 & 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

28"x1/2 ft. burned and sawn stump S.33°E., 61.3 ft.
3½ PK top center.
Note - Mon. 70' +/- on paved rock Cr. Rd. Course E-W
Area badly burnt 9/2020
Compass decl. 14½°E.
See sketch in file.
Lat: 43°21'34.86" N Long: 122°29'24.59" W