

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. ¼ Cor. for Sec. 25 only, T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note: Original ¼ Corner common for secs. 30, T25-2 and Sec. 25, T25-3, set by Laban Wheeler, contract #467 dated April 7, 1883 (DCSO records, Volume 9 Page 3586)

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11511)

Proportional Measurement, Set an iron post, 3 ft. long 1" dia. 28" in the ground for ¼ sec. cor. of sec. 25 only, with brass cap marked:

¼ S25
1943

from which

A Fir 12" dia., bears S.70°W., 51 lks., mkd ¼ S 25 BT.

A Fir 12" dia., bears N.20°W., 15 lks., mkd ¼ S25 BT.

FD 0k by DCSO June 1966 - C.S. File 54/27-170

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/17/2022 (Filed 4/14/2022) - C.S. File 67/52-20

Found - GL0 brass cap (properly mkd) protrudes 12" in rough stone mound.

Burnt, dead, 30" D.Fir S.70°W., 32.8 ft.. PK nail, right side center (Rec. 51 lks. 33.7 ft)

Stub & roots of Fir N.20°W., 9.9 ft.

New - 21" burnt dead cedar S.48½°W., 35.2 ft., 3½" PK nail, right side center.

22" burnt dead D.Fir S.10½°W., 37.2 ft., 3½" PK nail, right side center.

Note - Area burnt 9/2020

See sketch in file.

Lat: 43°21'59.69" N Long: 122°59'25.11" W