

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only. (East)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3586-7)

 Set cedar post 4 ft. long, 4" sq., 24" in the ground for corner to secs. 19, 24, 25 and 30 marked T.25S S19 on NE., R2W S30 on SE., R3W S25 on SW., S24 on NW faces with 4 notches on N and 2 notches on S edges, from which
 A Fir 40" dia. bears N.65°W., 65 lks. dist., marked T25S R3W S24 BT.
 A Cedar, 12" dia. bears S.40°E., 76 lks. dist., marked T25S R2W S30 BT.
 A Cedar 24" dia., bears S.44°W., 30 lks. dist., marked T25S R3W S25 BT.
 A Fir 45" dia., bears S.75°E., 9 lks. dist., marked T25S R2W S19 BT.

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11512)

 Point for the original sec. cor. which now refers to secs. 24 and 25 only, determined by reference to the record measurements from the old NE., SE., and SW. bearing trees, and record bearing from the old NW. bearing tree. At point for corner, set an iron post, 3 ft. long 2" dia., 28" in the ground, for cor. of secs. 24 and 25, with brass cap marked:

T25S	T25S
S24	R2W
S25	S19
R3W	

1943 from which

- A Fir 54" dia., bears N.69°E., 9 lks., with partial scribe marks on old bark blaze which I obliterate. (Old BT)
- A Red Cedar, 22" dia., bears S.32¼°E., 76 lks. mkd. T25S R2W S20 BT. I obliterate the marks on this old bearing tree.
- A Red Cedar 28" dia., bears S.44½°W., 30 lks. with blaze healed. I re-blaze and remark this old BT T25S R3W S25 BT.
- A Fir 56" dia., bears N.65°W., 36 lks., with partial scribe marks on old bark blaze. I reblaze and remark this old bearing tree T25S R3W S24 BT.

continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only. (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23331-2)

The cor. of secs. 24 and 25, T. 25 S., R. 3 W., on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground with a brass cap (properly) mkd.

from which the remains of the original bearing trees

A red cedar stump, 38" dia., bears S.44½°W., 19.8 ft., with illegible scribe marks visible on a partially healed, decayed blaze, and a tin cap.

A decayed Douglas fir stump, 57" dia., bears N.65°W., 23.8 ft., with a healed blaze.

and new bearing trees

A red cedar, 11" dia., bears S.67°E., 3.0 ft., mkd. T25S R2W S19 BT.

A D.Fir, 14" dia., bears S.34¼°W., 28.4 ft., mkd. T25S R3W S25 SC BT.