

PRIMARY CORNER DESCRIPTION W. ¼ Cor. Sec. 19, T 25-2

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23332)

The ¼ sec. cor. of sec. 19 only, on the W. bdy. of the Tp., perpetuated by the Douglas Co. Surveyor's Office in 1966 & 1995, monumented with an iron post, 1" dia., firmly set, projecting 8" above the ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

A decayed D.Fir stump, 36" dia., bears N.22°E., 36.3 ft., with illegible scribe marks visible on a partially opened, decayed blaze.

A D.Fir, 35" dia., bears S.21°E., 28.4 ft., with a healed blaze.

and remaining BT mkd. by the Douglas Co Surveyor's Office in 1966

A hemlock, 13" dia., bears N.88½°E., 39.1 ft., with a healed double blaze.

and BTs mkd. by the Douglas County Surveyor's Office in 1995

A hemlock, 14" dia., bears N.48½°E., 5.0 ft., with a healed blaze.

A D.Fir, 6" dia., bears S.76°E., 18.3 ft., with a healed blaze and a scar at waist height.

Corner is located approximately 1 ft. E. of the edge of a large boulder, 6 ft. x 4 ft. x 4 ft.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/20/2023 - C.S. File 67/56-37

Found - 2½" GLO 1943 brass cap (properly mkd) on 1" iron pipe up 14" in rough stone mound.

Rotted 15"x1½ ft. D.Fir stump N.22°E., 36.3 ft.

Burned, sawn 35"x3 ft. D.Fir stump S.23°W., 28.0 ft.

(rec S.21°E. 28.4 ft) add 3½" mag nail top center
13"x1½ ft burnt, sawn Hemlock stump N.88½°E., 39.1 ft. healed lower blaze.

17"x1 ft. burnt, sawn hemlock stump N.47°E., 4.9 ft.

(Rec N.48½°E. 5.0 ft) add 3½" mag nail top center

New - 14"x2 ft burned, sawn fir stump N.51°E., 18.5 ft., 3½" mag nail top center.

18"x2½ ft. burned, sawn Hemlock stump S.7°W., 13.0 ft. 3½" mag nail top center.

Note - Corner approx. 150' North of E-W gravel Rd.

Area burnt 9/2020

Compass decl. 14½°E.

Corner is on shallow ESE slope in large shovel logged clear cut.

Oregon Coordinate Reference System Cottage Grove -
Canyonville Zone N 199618.043 E 255498.875