

PRIMARY CORNER DESCRIPTION E. ¼ Cor. Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3587)

Set Cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ corner marked ¼ S on W face, from which
A Maple, 10" dia., bears N.23°E., 17 lks. dist., marked ¼ S BT.
A Cedar, 16" dia., bears S.46°E., 27 lks. dist., marked ¼ S BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11513)

Point for the original ¼ sec. cor. which now refers to sec. 24 only, determined by reference to the record measurements from both old bearing trees. At point for corner, Set an iron post 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 24 only, with brass cap marked:
¼ S24 |
1943 from which
A Red Cedar 22" dia., bears S.48½°E., 27 lks. mkd. ¼ S BT. I obliterate the marks on this old BT.
A Maple, 11" dia., bears N.16°W., 17 lks., with old blaze healed. (Old BT)
A Fir 50" dia., bears S.79½°W., 41 lks., mkd. ¼ S24 BT. (New BT)
A Fir 36" dia., bears N.15½°W., 49 lks., marked ¼ S24 BT. (New BT).

Douglas County Surveyors Office - Randall Smith & Stephen Flause - 4/3/95 -C.S. 64/63 -2

Found - 2½" GL0 Brass cap on a 1" OD Iron pipe, protrudes 1' above ground .
10" now 13" dia, 25' high maple snag, with a fully healed single blaze, bears N.16°W., 12' (rec. N.16°W., 11.2' dist possible face measurement) new sprouts growing from base.
16" now 24" dia, 2' high cedar stump, no blazes or scribing visible, bears S.48½°E., 17.8'.
50" now 50" dia, 2' high D.Fir stump, no blazes or scribing visible, bears S.79½°W., 27.1'.
36" now 36" dia, 6' high D.Fir stump, with a fully healed single blaze, bears N.15½°W., 32.3'.
New - 6" D.Fir, double blazed and scribed "¼ S24 CS BT", bears N.73°W., 26.3'. continued next page

PRIMARY CORNER DESCRIPTION E. ¼ Cor. Sec. 24 only

Alias	Description

<p>4" Hemlock, double blazed and scribed "X BT", bears N.1½°W., 23.7'. 12" Hemlock, double blazed and scribed "¼ S24 CS BT" on a single 5' high blaze, bears S.79°W., 11.6' (lower trunk is scared).</p>
<p>BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, under Group No. 2749 , surveyed Aug. 2014/April 2015 - (DCSO records Vol. 58 Page(s) 23332-3)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 24 only, T.25S., R.3W., perpetuated by the Douglas Co. Surveyor's Office in 1995, monumented with an iron post, 1" dia., firmly set, projecting 3" above the ground, with a brass cap (properly) mkd. from which the remains of bearing trees mkd. by Price in 1943-44</p> <ul style="list-style-type: none">A D.Fir stump, 54" dia., bears S.79½°W., 27.1 ft., with no marks visible.A decayed D.Fir stump, 38" dia., 5 ft. high, bears N.15½°W., 32.3 ft., with a healed blaze. <p>and BTs mkd. by the Douglas County Surveyor's Office</p> <ul style="list-style-type: none">A hemlock, 20" dia., bears S.77¼°W., 12.0 ft., with scribe marks S CS visible on a partially healed blaze at breast height.A D.Fir, 15" dia., bears N.74°W., 26.1 ft., with a healed blaze.A hemlock, 9" dia., bears N.2¼°W., 23.4 ft., with a healed double blaze.
<p>Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 1/27/2026 - C.S. File 67/62-07</p> <p>-----</p> <p>Found - 2½" GL0 brass cap on 1" iron pipe proj. 15". Very rotted - burned 50" x 3 ft. fir stump S.79½°W. 27.1 ft. Add 3½" mag nail top center. Burned - solid 27" x 5 ft. D. Fir stump. N.15½°W. 32.3 ft. face burned off. Add 3½" mag nail right side center. Burned - sawn 22" x 2 ft. hemlock stump S.77¼°W. 12.0 ft. healed blaze. Add 3½" mag nail top center. Burnt - sawn 19" x ½ ft. fir stump N.74°W. 26.1 ft healed blaze. Add 3½" mag nail top center. Burned - sawn 12" x 1½ ft. hemlock stump North 23.4 ft. (Rec. N.2¼°W.) Healed blaze partly scribe visible. Add 3½" mag nail top center.</p> <p>Continued next page</p>

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. ¼ Cor. Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mon. Bent 1 ft. to west. Reference and reset mon. to plumb position projecting 15". Add large mound of stone.

Notes - Area burnt 9/2020
Mon. on gentle East slope near East edge of square mile clearcut.

Compass decl. 14¼°E.
TRIMBLE GEO XT LOCATION
43.38166156° N. 122.98931837° W.