TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. ¼ Cor. Sec. 13 only

Alias Description
Alias Description
Alias Description
Alias Description

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3588)

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11515)

Proportional measurement. Set an iron post 3 ft. long, 1" dia., 12" in the ground, to bedrock, and in a mound of stone to top, for ¼ sec. cor. of sec. 13 only, with brass cap mkd.

¼ S13
1943

from which

A Sugar pine, 12" dia., bears S.13°W., 6 lks. dist., mkd. ¼ S13 BT.
A Fir 14" dia., bears N.49½°W., 65 lks. dist., mkd. ¼ S13 BT.

Doug. Co. Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - July/Aug. 1966 - C.S. File 54/27-179

Found - GLO brass cap mkd. "¼ S13/1943".
12" now 16" Sugar pine, S.13°W., 4.0 ft. appears to be dying, shows very good scar. Do not open.
14" now 20" D.Fir N.49½°W., 42.9 ft. Alive & in good condition. Shows very good scar. Do not open.
New BT - 7" D.Fir S.10°W., 18.8 ft. mkd. ¼ S13 CS BT.
This corner lies at bottom of 20 ft. high rock bluff, course NW-SE on very steep, SW slope.