

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700573

PRIMARY CORNER DESCRIPTION CC Sec. 6 & 7 only (West), T25-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Pages 11517-18)

-----  
Proportional measurement. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.

	T25S	S6	CC
	R3W	S7	
	S12	R2W	
	1943		

from which  
A Fir 30" dia., bears N.50 3/4°E., 23 lks. dist., mkd.  
T25S R2W S6 CC BT.  
A Fir 32" dia., bears S.20½°E., 21 lks. dist., mkd.  
T25S R2W S7 CC BT.

Douglas Co. Surveyors Office - Vernon Tracy; Jack Heritage August 1966 - C.S. File 54/27-175 (C.S. 54/27-168 fd)

-----  
Found - GL0 brass cap mkd. in 1943.  
30" now 34" Fir, 6 ft. high stump, N.50 3/4°E., 15.2 ft. scribe marks visible on nearly healed blaze.  
32" now 36" Fir, 6 ft. high stump, S.20½°E., 13.9 ft. blaze nearly healed.  
New BTs- Mark only available trees.  
8" Yew S.63°E., 168.2 ft. mkd. T25S R2W S7 CC CSBT.  
12" Hemlock N.7°E., 222.3 ft. mkd. T25S R2W S6 CC CS BT.  
Corner lies in old logged off area.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - Sept. 25, 1997 - C.S. 64/78-7

-----  
Found- 2½" brass cap on a 2" O.D. iron pipe protrudes 12" above ground.  
30" now 34" dia. 6' high D.Fir stump, with illegible scribing on a partially healed single blaze, bears N.50 3/4°, 15.2' (agrees with rec.) 1940 GL0.  
32" now 36" dia. 5' high D.Fir stump, with scribing "T25S R2" visible on a partially healed single blaze, bears S.20½°E., 13.9' (agrees with rec.) 1940 GL0.  
(Area around corner is over grown with brush Brg's and dist's to 1966 DCSO BT's not checked.)

Cont. next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700573

PRIMARY CORNER DESCRIPTION CC Sec. 6 & 7 only (West), T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now 10" dia. Yew, with a partially healed double blaze, scribing visible "25S R2W S7 CC CS BT", (rec. S.63°E., 168.2') 1966.  
12" now 26" dia. Hemlock, with illegible scribing visible on a partially healed double blaze, (rec. N.7°E., 222.3') 1966.  
New - 10" dia. D.Fir, double blazed and scribed "T25S R2W S6 CC CS BT", bears N.66½°E., 6.4'.  
7" dia. D.Fir, double blazed and scribed "T25S R2W S7 CC CS BT", bears S.12½°E., 36.3'.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2317, Surveyed June 2010/June 2011 - DCS0 records Vol. 57 Page(s) 22791-2

-----  
The closing cor. of secs. 6 & 7 only, on the W bdy. of the Tp perpetuated by the Douglas Co. Surveyors Office in 1966, further perpetuated by the Douglas Co. Surveyors Office in 1997, monumented with an iron post, 2" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.  
from which the remains of bearing trees mkd. by Price  
A sawed, decayed fir stump, 36" dia., bears N.50¾°E., 15.2 ft., with scribe marks T25S R2W S6 visible on fragment of a partially healed blaze.  
A sawed, decayed fir stump, 35" dia., bears S.20½°E., 13.9 ft., with scribe marks T25S R2 visible on a partially healed blaze.  
and BTs mkd. by the Douglas County Surveyors Office in 1966  
A hemlock, 29" dia., bears N.6°E., 221.7 ft., with a healed blaze.  
A yew, 11" dia., bears S.62¾°E., 169.5 ft., with fragmentary scribe marks visible on a partially healed blaze.  
and BTs mkd. by the Douglas County Surveyor's Office in 1997  
A fir, 15" dia., bears N.66¾°E., 6.8 ft., with a healed double blaze.  
A fir, 10" dia., bears S.12¾°E., 36.5 ft., with a healed double blaze.

Fd. as per 2011 BLM survey by D.Edwards, 7/2013 M165-53

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/14/2023 - C.S. File 67/57-28

-----  
Found - 2" GLO brass cap (properly mkd) proj 12"  
Burned, rotted 27"x5½ ft. Fir stump N.50¾°E., 15.2 ft., blaze gone. Continued next page

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 700573

PRIMARY CORNER DESCRIPTION CC Sec. 6 & 7 only (West), T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burned, rotted 27"x6 ft. Fir stump S.20½°E., 13.4 ft. (rec. 13.9 ft) blaze gone.

Burned, sawn 32"x 2 ft. Hemlock stump N.6°E., 221.7 ft. low blaze scar.

Burned, dead 14" yew S.62¾°E., 169.5 ft., fragmentary scribe visible on partly healed blaze, add 3½" mag nail rt side center.

Burned, dead 19" Fir N.66¾°E., 6.3 ft. (rec. 6.8 ft) healed double blaze, add 3½" mag nail right side center.

Burned, dead 13" Fir S.12¼°E., 36.5 ft. healed double blaze add 3½" mag nail right side center.

New - Burned sawn 12"x 3 ft. hemlock stump, N.79°W., 21.6 ft. 3½" mag nail top center.

Note - Area burnt 9/2020  
Mon. is in NW cor burned second growth 50' east of gravel road.

Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 212684.152      E 255396.871