

PRIMARY CORNER DESCRIPTION E ¼ Cor. Sec. 1 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3591)

Set Dogwood post, 3½ ft. long, 3 x 4 inches, 18" in the ground, for ¼ sec. cor. marked ¼ S on W face, from which
A Fir 6" dia., bears N.71°W., 30 lks. dist., marked ¼ S BT.
A Fir 10" dia., bears S.38°E., 40 lks. dist., marked ¼ S BT.

GL0 Dependent Resurvey by Norman D. Price, Under Special Instructions dated April 5, 1940 (DCSO records, Volume 27 Page 11519)

Point for original ¼ sec. cor. which now refers to sec. 1 only, determined by reference to the record bearing and distance from the original SE bearing tree.
At point for corner, Set an iron post, 3 ft. long, 1" dia., 18" in the ground to bedrock, and in a mound of stone to top, for ¼ sec. cor. of sec. 1 only, with brass cap mkd. ¼ S1|
1943
from which
A dead Hemlock 12" dia., bears S.38°E., 40 lks. dist., mkd. ¼ S BT. I obliterate the marks on this old bearing tree.
A Fir 42" dia., bears S.7°W., 61 lks. dist., marked ¼ S1 BT. (New BT)
A Hemlock 8" dia., bears N.75°W., 16 lks. dist., mkd. ¼ S1 BT. (New BT)

Doug. Co. Surveyors Office - Vernon Tracy; Joe Brady; Jack Heritage - June/July 1966 - C.S. File 54/27-177

Found - GL0 brass cap mkd "¼ S1/1943" bent over. Straighten & reset in mound of stone.
NW BT gone, stumps of SE & SW BTs remain.
New BT - 12" Fir, snag 15 ft. high N.73°W., 39.4 ft. mkd. ¼ S1 CS BT.
No live trees available. Corner lies on very steep, N. slope, 10 ft. N. of rock face 6.0 ft. high x 25 ft. long, course E & W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 12/9/2024 - C.S. File 67/59-26

Reported as not found.
Logged, burned, very steep, checked widely with pin finder.