

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Dennis Hathorn under Contract dated September 1856

Set stone post 18 x 8 x 3, from which
A W.Oak 20" dia. bears S.71°E., 112 lks.

Victor McLind - For: Merrill Bullock - Dec. 1971 (added
6/21/2016) - M44-7

Found - 3"x8" stone in N-S fence.
OBT 24" W.Oak sang with rotted face, bears
S.71°E., 73.6 to face.

Douglas Co. Surveyors Office - R.B. Kimberling - P.L. Earle -
May 23, 1977 (added 6/21/2016) - C.S. File 59/34-23

Condition report only
Found - A 13"x10"x4" sandstone rock (rec. 18x8x3) at fence
corner approx 50 yrs old N.S. fence, 30 yr old
fence to east. Rock was pointed out by
interested landowner, L. Pratt, as corner
accepted by V. McLind, Licensed Surveyor (ref
M44-7). Rock was apparently set in location;
digging in general are uncovered only basaltic
river washed rocks of smaller size.
A W.Oak, orig. 20" now 24" snag bears S.74°E., 74.6
ft. (orig. S.71°E., 73.9 ft.) any marking
completely destroyed by old chopping 9" deep
and partially grown over.
Note - The orig. line call to Calapooya Cr. appears good.
No monument set, no conclusive evidence.
Dec. 20°.

Douglas Co. Surveyors Office - Randall Smith; Stephen Flauser
April 14, 1987 - C.S. File 62/40-11

Found - 3" x 10" x 13" stone buried with top protruding 3"
above ground. Possible original monument.
20" now 21" dia. 15 ft. high snag, previously
opened, we find older axe marks & small pieces
of blaze with no scribing, bears S.75°E., 75.1
ft. (Rec. S.71°E., 73.9 ft distance a possible
face measurement.

continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 037020

PRIMARY CORNER DESCRIPTION N NW Cor. Iles DLC #37

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

We monument the position of stone as the most probable location of the orig. NNW DLC 37 corner based on the following observations: Stone appears to be a locally accepted corner. It is the intersection point of an old northerly-southerly and easterly fence line. Stone was tied in survey (M44-7) by V. McLind as the DLC corner. The orig. call of Calapooya Creek to the east checks out well. The position of stone fits well with other gov't corners in area (SE cor DLC #46 and section corner for 1, 6, 12, 7. (See computations in CS File folder.)

Set - 2 3/8" dia. brass cap on a 1" inside dia. x 32" long pipe protruding 8" above ground. Reset 3" x 10" x 13" stone along east edge of I.P. protruding 3" above ground. Cap stamped:

DOUGLAS COUNTY SURVEYORS

R T25S

4 NNW

DLC

37

1987

Office

New BTs- 9" D.Fir double blazed and scribed "NNW DLC 37 CS BT" bears N.81 3/4°E., 25.9 ft.

12" I.Cedar double blazed & scribed "NNW DLC 37 CS BT" bears N.51 1/2°W., 31.8 ft.

Double trunked Myrtle with scribing on east 9" trunk, double blazed & scribed "NNW DLC 37 CS BT" bears S.9°E., 47.5 ft. to center of root crown.

Corner lies approx. 300 ft. north of Fair Oak Community Church at the intersection of a northerly-southerly and easterly fence line. Cor. lies approx. 140 ft. south of Calapooya Ck.

Found OK by C. Sweeden, Jan. 2002 - M139-39