

PRIMARY CORNER DESCRIPTION SE Cor. Odle DLC #41

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Dennis Hathorn - Contract dated Sept. 1856  
-----

Set post S E cor Claim 41, from which  
A Laurel 10" dia. bears N.62°W., 54 lks.  
An Oak 15" dia. bears S.48°W., 60 lks.

Ben B. Irving, Dep. Co. Surveyor, For: State of Oregon  
N.E. Richardson; Robert Helliwell; Harvey Eppstein, Jr.  
June 22, 1939 - C.S. File 37/204 and M 5 - 66  
-----

Corner identified from an Oak which shows axe marks but is badly rotted and no scribe marks could be found. Using this as the orig. BT which was an oak, 15" dia. S.48°W., 60 lks. it would place the SE cor. N.89°47'E., 1935.8 ft. from the SW corner of the Claim and South 4878.5 ft. from the NE cor. This does not check the original lengths of these lines but does check the original bearing very close.  
Drove a 3/4" x 24" pipe for the corner 18" in the ground.  
A Fir 24" dia. bears S.70°E., 56 lks. blazed & scribed  
SE. D.L.C. 41 C.S.B.T.  
A Fir 50" dia. bears N.21°E., 83 lks.

A. Boyer, Deputy Co. Surveyor - For: Bonanza Mines, Inc.  
Feb. 1941 - M 4-25 and C.S. 34.39  
-----

All trees cut for mine properties.  
3/4" Pipe.  
36" Fir stump, tack on top and SW face, N.57°E., 61.7 ft.  
Copco Pole #A 3503, N.11 3/4°W., 100.9 ft., (on slope)

BLM dependent resurvey by Wayne L. Rogers, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1755 surveyed June/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19902-3)  
-----

From the SE. cor. of DLC 41, perpetuated by Irving, Deputy County Surveyor, in 1939, from original evidence no longer in existence, further perpetuated by Boyer, Deputy County Surveyor, in 1941, both recorded in the Douglas County Surveyors Office file for this Tp., point identifier No. 041060; monumented with an iron pipe, 1 1/4" diam., firmly set, projecting 3" above ground (alongside of which is an iron rod, 1" diam., firmly set, projecting 2 " above ground), from which the remains of bearing trees mkd. by Irving:  
A sawed fir stump, 53" diam., bears N.20 3/4°E., 86 lks., no marks visible.  
A decayed fir stump, size indeterminate, bears S.70 1/2°E., 57 lks., no marks visible. continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 041060

PRIMARY CORNER DESCRIPTION SE Cor. Odle DLC #41

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and the remains of accessories by Boyer  
A sawed fir stump, 39" diam., bears N.58°E., 95 lks., no marks visible.  
A power pole, 12" diam., bears N.12°W., 153 lks.  
At the corner point  
Set a stainless steel post, 28 " long, 2½ " diam., 25 " in the ground directly over the iron pipe, with brass cap mkd.  
T25S R4W  
C41  
S16  
1995  
from which new bearing trees  
A madrone, 12" diam., bears S.35½°W., 14 lks., mkd. S16 BT  
A fir, 14" diam., bears N.35 3/4°W., 10 lks., mkd. C41 BT.  
Deposit the iron rod inside and a white "DEEP-1" magnetic marker at base of stainless steel post.