TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 048020

PRIMARY CORNER DESCRIPTION NW Cor. Driver DLC #48

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, contract dated Sept. 1856

Set stone post 6 x 8 x 18" , from which
An Oak 18" dia. bears S.79°E., 810 lks.
An Oak 15" dia. bears S.¼°W., 633 lks.

M.B. Germond - Wit. Thomas Harvey; R.H. Manning; John Abeene; Roland Corkran - Jan. 25, 1917 - Field Book 42 Page 22

I intersected lines. Set in sandstone 4" x 14" x 28", from which:
A W.Oak 12" dia. bears S.17½°W., 4.78 chs.
A W.Oak 10" dia. bears S.76°10'E., 3.66 chs.

Vernon R. Tracy - Mike Darby - Jack Barnett - January, 1965 C.S. File 53/47-45

Found - 12" now 18" W.Oak S.17½°W., 315.5 ft., shows good scar, we rescribe: "N.W. DLC 48 CS BT."
10" now 16" W.Oak S.76°E., 241.5 ft., open & find "C S D" scribe. Remark "NW. DLC 48 CS BT", as there is no other tree available.
No trace of stone called for.
Set brass cap at cor. mkd: County Surveyors Office, 1965
T25S R4W N.W. DLC 48
This cor. lies in road under a gate in a N-S fence , 4.0 ft. North of south gate post about 4" below ground surface.

Doug. County Surveyors Office - Randall Smith; Stephen Flause May 21, 1992 - C.S. File 64/26-9

Found - 2½" DCSO brass cap on iron pipe 4" below ground.
12" now 21" dia. double blaze on north trunk, bears S.16½°W., 318.4 ft. to center of root crown. (Rec. S.17½°W., 315.5 ft.) (1917)
10" now 17" dia. multi trunked W.Oak with a previously opened blaze on north trunk, no scribing visible; north trunk bears S.76°E., 241.5 ft. (agrees w/rec. 1917)
New BTs - 11" dia. W.Oak double blazed and scribed "NW DLC 48 BT" bears S.49°E., 267.2 ft.
11" dia. W.Oak double blazed & scribed "NW DLC 48 CS BT" bears S.08°W., 155.0 ft.