

PRIMARY CORNER DESCRIPTION S SE Cor Deardorff DLC #50

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Dennis Hathorn under Contract dated Sept. 1856 ----- Set post S E Cor claim - from which An Oak 30" dia. bears S.81°E., 130 lks. An Oak 12" dia. bears N.12°W., 73 lks.	
Lloyd D. Smith, For: Oregon State Board of Forestry March 30, 1983 - M 94-1 ----- Set - 5/8" x 30" Iron rod with plastic cap 28" in ground. BTs - 26" Fir N.12½°E., 84.6 ft. 9" Oak S.75½°E., 63.2 ft. Woven wire fence North 53.0 ft. course N.36°W. by S.36°E.	
Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - Aug. 14, 1997 - C.S. 64/75-35 ----- Found - 5/8" I.R. protrudes 1" above ground bent south westerly. 1983 No OBT's found 26" now 31" dia. D.Fir, with a fully healed single blaze, bears N.12½°E., 85.4' (rec. N.12½°E., 84.6' dist. Is to face) 1983 9" Oak now 17" dia. Ash, with a fully healed single blaze, bears S.75½°E., 63.8' (rec. S.75½°E., 63.2' dist. is to face) 1983. 2 3/8" dia. Brass cap on a 1 3/8" O.D. by 32" long iron pipe is set at plumb position of found I.R. set flush with ground. Fd. I.R. is set along north edge of Bc/Ip 3" below ground. New - Multi trunked Hawthorn single blazed and scribed "X BT" 3½' above ground on 6" dia. S'Wly trunk, bears N.46½°E., 39.6'. 18" dia. W.Oak, double blazed and scribed "SSE DLC 50 CS BT", bears N.43°W., 35.5'.	
Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/1/2002 - C.S. File 66/32-41 ----- Found - 1997 DCSO brass cap/iron pipe flush with ground. 26" now 32" dia., D.Fir with a fully healed single blaze, bears N.12½°E., 85.4 ft. (1983) 9" Oak now root hole bears S.75½°E., 63.8 ft. (1983) 1997 NE BT now gone. 18" now 19" dia., W.Oak with visible scribing on a partially healed double blaze, bears N.43°W., 35.5 ft. (1997) continued next page	

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 050040

PRIMARY CORNER DESCRIPTION S SE Cor Deardorff DLC #50

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 8" dia., W.Oak double blazed & scribed "SSE DLC 50
CS BT" bears S. bears S.53½°E., 228.0 ft.
Set metal fence post North 1 ft.
Compass decl. 17½°E.