

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records, volume 9 Page 3738)

-----  
Set ¼ sec. post, from which  
    A B.Oak 18" dia. bears N.29°E., 236 lks. dist.  
    A B.Oak 40" dia. bears S.38°E., 225 lks. dist.  
Stratton's house bears S.12°W., 20 lks. dist.

Doug. Co. Surveyors Office - Gary L. Langlitz; P. Earle -  
January 18, 1974 - C.S. File 56/43-6

-----  
Found - Possible orig. SE BT (?). Ground depression and  
          parts of oak roots in place. Depression large  
          enough to have had 40" Oak in place. No other  
          large trees in vicinity. No other evidence.  
Note - Location found by proportioned location from State  
          Forestry crew proportioned from W¼ of 18 & NE  
          sec. cor. Sec. 18. NW corner of Sec. 18 gone.  
          Proportioned using record bearings & distances  
Area has been reportedly logged & burned several times. Call  
to ridge top fits well according to S.F. Location fits well  
on aerial. E-W fence intersects road approx. 75 ft. south of  
approx. location. S.F. location is at west edge of roadway.  
Original NE BT would fall in roadway.  
I DO NOT RENEW.

Oregon State Board of Forestry, Lloyd D. Smith - March 30,  
1983 - M 94-1

-----  
Set - Oreg. St. Bd. of Forestry 1½" x 36" alum. pipe with  
      3½" alum. cap with magnetic insert, 34" in  
      ground.  
BTs - 18" Fir N.67°W., 87.8 ft.  
      11" oak S.57¼°E., 28.5 ft. with yellow metal  
      location poster.  
BOs - 4"x4"x72" White painted Cedar post bears S.48°W.,  
      1.5 ft  
Gravel road 8 ft. wide east 11.0 ft. course N.33°E., by  
S.33°W.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Mike  
Koch - Jan. 21, 2016 (Filed 3/17/2020) - C.S. File 67/46-15

-----  
Found - 1" i.d. iron pipe by Smith in 1983, firmly set,  
          projecting 4" with a 3 3/4" diam. aluminum cap  
          projecting 4" above the ground (properly) mkd  
continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BTs by Lloyd D. Smith 1983 -

A 12"x3" Tall Oak stump bears S.57¼°E, 28.5 ft. cut below blaze.

A 27"x1¼' Tall D.Fir stump bears N.67°W, 87.8 ft. with open lower blaze partial scribing visible.

A 4"x4" Cedar Post bears S.48°W., 1.5 ft.

New BTs- A 7" W.Oak bears N.66°E, 65.7 ft. scribed "¼ SEC7 CS", "BT"

A 5" W.Oak bears S.19½°E, 26.4 ft. scribed "X", "CSBT"

A 8" B.Oak bears S.62½°W, 14.7 ft. scribed "¼ S18", "CSBT"

A 4" W.Oak bears N.6¼°W., 7.8 ft. scribed "X", "BT"

Note - All bearing trees have BT tags attached. All new bearing trees have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.

Monument falls near the west shoulder the 8 ft. wide gravel Plat B Road on a flat to rolling slope in a oak, ash, fir and madrone woodland and just west of the foot of a moderate NW slope.

Compass decl. 15°E.