

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 160400

PRIMARY CORNER DESCRIPTION E. 1/16 Cor. for Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 1957 and July 1958 (DCSO records, Volume 29, Page 12315)

Set an iron post, 28" long 2½" dia. 26" in the ground, with brass cap marked: S 18

E 1/16 S 19
1957

from which

A Fir 27" dia. bears N.74°W., 83 lks. dist. marked
E 1/16 S18 BT.

A Fir 25" dia. bears S.44°45'E., 124½ lks. dist., marked
E 1/16 S19 BT.

From this point, a stone 24 x 36" protruding 12" above ground, with chisel marks X SL&W SW COR on upturned face, bears SW., 7 lks. dist., from which a bearing tree:

A Fir snag 37" dia. bears S.66°E., 47 lks. dist. with scribe marks SL&W BT.

Doug. Co. Surveyors Office - Ray Tracy; Mike Darby; Jack Barnett - Jan/Feb 1965 - C.S. File 53/47-4

Found - 1957 BLM brass cap and one live BT., other BT, down & out of position:
25" now 26" Fir S.44 3/4°E., 82.2' face grown over.
Do not open.

27" now 29" Fir N.74°W., 54.8 ft. lying face up, dead.

New BT - 11" D.Fir N.18°E., 100.8 ft. mkd: E 1/16 S18 CS BT.