

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6 of T26-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3734)

Set post cor. of secs. 5, 6, 31 and 32, from which
A B.Oak 30" dia. bears N.35°E., 75 lks. dist.
A B.Oak 24" dia. bears N.31°W., 71 lks. dist.
A B.Oak 20" dia. bears S.34°W., 150 lks. dist.
A B.Oak 10" dia. bears S.69°E., 58 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 (DCSO records, Volume 29 Pages 12306-07)

Corner determined at record bearing and distance from the
original bearing trees as follows:

A B.Oak 35" dia. bears N.35°E., 75 lks. dist. marked
with a healed blaze.
A down & rotted B.Oak 14" dia. bears S.69°E., 58 lks.
dist., no scribe marks visible.
A down 7 rotted B.Oak 30" dia. bears S.34°W., 150 lks.
dist., with scribe marks S6 BT visible on opened
blaze.
A down 7 rotted B.Oak 30" dia. bears N.31°W., 71 lks.
dist., no scribe marks visible.
At the corner point, set an iron post, 28" long 2½" dia. 24"
in the ground with brass cap mkd: T25S R4W
 S 31 | S 32
 S 6 | S 5
 T26S
 1957 from which
A W.Oak 10" dia. bears N.66°E., 20 lks. dist. marked
T25S R4W S32 BT.
A W.Oak 10" dia. bears S.27½°E., 44 lks. dist. marked
T26S R4W S5 BT.
A W.Oak 10" dia. bears S.32°W., 44 lks. dist. marked
T26S R4W S6 BT.
A W.Oak 11" dia. bears N.63½°W., 23 lks. dist. marked
T25S R4W S31 BT.