

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #52 dated June 1871
(DCSO records, Volume 9 Page 3755)

Marked A Fir tree, 24" dia., for post cor. to secs. 19,
20, 29 and 30, from which

- A Laurel, 30" dia. bears N.48°E., 65 lks. dist.
- A Laurel, 18" dia. bears S.45°E., 20 lks. dist.
- A Laurel, 14" dia. bears S.48°W., 30 lks. dist.
- A Laurel, 14" dia. bears N.50°W., 31 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - (DCSO records, Volume 29 Page 12309)

Cor. determined by the original corner tree, a Fir, 45" dia.
with healed blazes in each of the four quadrants; from which
the original bearing trees, as follows:

- A down Madrone 31" dia. bears N.48°W., 65 lks. dist., no
scribe marks visible.
- A down Madrone, 16" dia. bears S.45°E., 21 lks. dist.
with a rotted blaze; no scribe marks visible. (Rec.
calls for a Laurel)
- A Madrone stump hole, bears S.48°W., 30 lks. dist.
- A Fir 20" dia. bears N.50°W., 31 lks. dist., with T2
RW S19 visible on opened blaze. (The rec. calls for
a Laurel)
- New BTs - A Fir 32" dia. bears N.51°E., 130 lks. dist. marked
T25S R4W S20 BT.
- A Fir 18" dia. bears S.49½°E., 104 lks. dist. marked
T25S R4W S29 BT.
- A Fir 10" dia. bears S.19°45'W., 158 lks. dist.
mkd. T25S R4W S30 BT.

Doug. Co. Surveyors Office - Milo Godfrey; V. Tracy & M Stone
Feb. 27, 1964 - C.S. File 53/47-21

Found - Corner tree, uprooted & rolled downhill approx.
20 ft. NW of corner.
20" Fir N.50°W., 20.5 ft. uprooted & down.
32" Fir N.51°E., 85.8 ft. uprooted & down, scribing
visible on face.
10" Fir S.19 3/4°W., 104.3 ft. now dead snag,
scribing visible on face.

(Continued Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

22" D.Fir S.49½°E., 68.6 ft. alive & in good condition, scribe visible on partially healed face.
 Set - (In hole left by uprooted corner tree): Brass cap
 Mkd: County Surveyors Office, 1964 T25S R4W S19|S20
 S30|S29
 New BTs - 14" D.Fir S.37°W., 78.8 ft. mkd: T25S R4W S30 CSBT.
 16" D.Fir N.20½°W., 47.5 ft. mkd: T25S R4W S19 CSBT.
 20" D.Fir N.80°E., 75.0 ft. mkd: T25S R4W S20 CS BT.
 Corner lies on very steep west slope approx. 100 ft. West of top of ridge.

Bureau of Land Management Dependent Resurvey - Jelley and Rogers - Group #1084, Survey, Jan./June 1982 (DCSO records Volume 45 Page 17522-23)

 Found - 1964 County brass cap.
 A root hole, bears S.45°E., 21 lks. dist. with an uprooted madrone alongside, 16" dia., no marks visible on decayed blaze. (Orig. BT)
 A root hole, bears N.50°W., 31 lks. dist. with an uprooted Fir alongside, 20" dia. with scribe marks T2 R4W S19 visible on open blaze. (Orig.)
 A root hole, bears N.51°E., 130 lks. dist. with an uprooted Fir alongside, 32" dia. with healed blaze. (1957)
 A sawed Fir stump 20" dia. bears S.49½°E., 104 lks. dist., with healed blaze. (1957)
 A Fir snag, 10" dia. bears S.20 3/4°W., 158 lks. with fragmentary scribe marks visible on partially healed blaze. (Rec. S.19¾°W.) (1957)
 A Fir 23" dia. bears N.80°E., 113 lks. dist. with healed blaze. (Godfrey)
 A Fir 19" dia. bears S.37°W., 119 lks. dist. with healed blaze. (Godfrey)
 A Fir 16" dia. bears N.20 3/4°W., 71 lks. dist. with healed blaze. (Godfrey)
 A Fir 13" dia. bears S.18 3/4°E., 59½ lks. dist. with healed blaze. (Unrecorded)
 New BTs - A Fir 7" dia. bears N.35¾°E., 45 lks. dist. mkd. T.25S R4W S20 BT.
 A Fir 8" dia. bears S.29½°W., 35½ lks. dist. mkd. T25S R4W S30 BT.