

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records, Volume 9 Page 3739)

-----  
Set post cor. of secs. 17, 18, 19 and 20, from which  
A Fir 80" dia. bears N.32°E., 27 lks. dist.  
A Fir 8" dia. bears N.60°W., 28 lks. dist.  
A Fir 8" dia. bears S.40°E., 64 lks. dist.  
A Fir 50" dia. bears S.57°W., 62 lks. dist.

Wilford N. Haines - For: Mt. Baldy Lumber Co. - February 15,  
1956 - M 2-14

-----  
Found 2 orig. BTs:  
Fir, S.40°E., 64 lks. and Fir, S.57°W., 62 lks.  
80" Fir down.  
Set 36" angle iron with brass cap at corner inscribed, Survey  
Point - Wilford Haines #239.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin  
and Roseberry - Special Instructions dated July 8, 1957 and  
July 15, 1958 - (DCSO records, Volume 29 Page 12313-14)

-----  
The cor. is determined at record distances from the remaining  
original bearing trees:

An uprooted Fir snag, 80" dia. bears N.32°E., 27 lks.  
with no marks remaining on a burned out blaze.  
A Fir 36" dia. bears S.42°E., 64 lks. mkd with healed  
blaze; also bark scribed S 8 visible.  
A Fir 59" dia. bears S.54¼°W., 62 lks. mkd with a healed  
blaze; also bark scribed S 19 visible.

At the corner point, set an iron post 28" long 2½" dia. 24"  
in the ground, with brass cap marked: T25S R4W

S 18 | S 17  
S 19 | S 20

1957 from which

A Fir 32" dia bears N.61°E. 138½ lks mkd T25S R4W S17 BT  
A Fir 13" dia. bears N.70°W., 57 lks mkd T25S R4W S18 BT  
From this point, an angle iron, 1 x 1" protruding 8" above  
ground, bears S.80°E., 3½ lks. dist., with brass cap marked,  
"Wilford N. Haines, #239 Survey Point, Drain, Ore."

Fd. Ok. 1982 BLM Resurvey - Jelly/Rogers - DCSO records,  
Volume 45 Page 17527)

continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2748, surveyed July 2014 - (DCSO records Vol. 58 Page 23174 & Plat 25-4 2015-1a&b)

-----  
The cor. of secs. 17, 18, 19, and 20, monumented iron post, with an 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.

from which the remaining original bearing tree

A fir, 39" dia., bears S.42°E., 42.2 ft., with a healed blaze.

and BTs mkd. by Zirpel, Roseberry, and Corbin in 1957-58

A fir, 38" dia., bears N.61°E., 90.4 ft., with a healed blaze.

A fir, 30" dia., bears N.70°W., 36.3 ft., with a healed blaze.

and a new bearing tree

A fir, 12" dia., bears S.73°W., 27.5 ft., mkd. T25S R4W S19 BT.

From this cor., a point established by Haines, PLS No. 239, in 1956, bears S.80°E., 2.3 ft., monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 6" above ground, with a brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE.