TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias Description
Alias Description
Alias Description
Alias Description

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records, 3739)

Set ¼ sec. post, from which
A W.Oak 8" dia. bears S.80°E., 85 lks. dist.
A W.Oak 8" dia. bears S.21°W., 51 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 1957 to July 1958 - (DCSO records, Volume 29 pages 12316-17)

Point for the cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia. 14" in the ground, to solid rock, in a mound of stone, 3 ft. base to top, with brass cap marked; T25S R4W

¼
S 18|S 17
1957

from which
A Fir 22" dia., bears N.69½°E., 52 lks. dist. marked ¼ S17 BT.
A Fir 26" dia. bears N.48 3/4°W., 115½ lks. dist. marked ¼ S18 BT.

Fd. & used on BLM dependent resurvey by Wayne L. Rogers, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1755 surveyed June/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19900)

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2748, surveyed July 2014 - (DCSO records Vol. 58 Page 23174 & Plat 25-4 2015-1a&b)

The ¼ sec. cor. of secs. 17 & 18, monumented with an iron post, 2½" dia., firmly set, projecting 4" above a mound of stone, 3 ft. base, I ft. high, with brass cap (properly) mkd. from which BTs mkd. by Zirpel, Roseberry, and Corbin in 1957-58
A fir, 32" dia., bears N.69½°E., 34.3 ft., with a healed blaze.
A fir, 33" dia., bears N.49¾°W., 76.2 ft., with a healed blaze.
Corner is located under a barbed wire fence extending N & S.