

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Goardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9, Page 3737)

Set post cor. of secs. 5, 6, 7 and 8, from which
A W.Oak 15" dia. bears N.27°W., 116 lks. dist.
A W.Oak 24" dia. bears N.8°E., 198 lks. dist.
A W.Oak 12" dia. bears S.71°W., 212 lks. dist.
A W.Oak 30" dia. bears S.1°E., 365 lks. dist.

M.B. Germond - Wit. Thomas harvey; John Abeen; R.H. Manning
and Cockran - Jan. 23, 1917 - Field Book 42 page 20

Reset corner from original bearing trees. Set in Sandstone
6" x 8" x 16", from which
W.Oak 30" dia. bears S.1°E., 368 lks. (Orig.)
W.Oak 12" dia. bears S.69°55'W., 216 lks. (Orig.)
W.Oak 15" dia. bears N.29°20'W., 118 lks. (Orig.)
W.Oak 8" dia. bears N.46°E., 40¼ lks.
SW Cor of DLC #48 bears S.89°20'E., 4.75 chs.

Vernon R. Tracy, Deputy - M. Darby and J. Barnett November
1964 - C.S. File 53/47-57

Found - Sandstone 6" x 8" x 12" buried & 2 original BTs.
12" now 30" W.Oak S.70°W., 142.6 ft., find reverse
"S" scribe.
15" now 34" W.Oak N.29°20'W., 77.9 ft. shows very
faint scar. Did not open.
Set brass cap at cor. mkd: County Surveyors T25S R4W S 6 | S 5
Office, 1964 S 7 | S 8
New BTs - 34" W.Oak N.29°W., 77.9 ft. (Orig.) marked:
T25S R4W S6 CS BT.
15" W.Oak S.14°W., 94.1 ft. mkd: T25S R4W S7 CS BT.
This tree has fence on South side.
12" W.oak S.15°E., 89.6 ft. mkd: T25S R4W S8 CS BT.
No trees close to N.E.
Most westerly guy ring on P.P.&L. line bears N.50°E., 90.2 ft.

Found OK, D. Bentz, November 1987 - M 105-17
Found OK, D. Peel, August 1992 - M 115 - 62
Fd. Ok C. Sweeden, 7/2006 - 2006-0080