

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 220300

PRIMARY CORNER DESCRIPTION W. 1/16 Cor. for Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 8, 1957 and July 15, 1958 - (DCSO records, Volume 29 page 12310-11)

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked: S 20

S 1/16 S 29

1957

from which

A Fir 29" dia. bears N.44½°W., 44 lks. dist. marked
W 1/16 S20 BT.

A Fir 18" dia. bears S.22½°W., 106 lks. dist. marked
W 1/16 S29 BT.

Doug. Co. Surveyors Office - Karen Reed; S.J. Flause - Oct. 3, 1978 - C.S. File 60/17-11

Found - 1957 BLM brass cap on a 2" pipe 1" above ground.
32" Fir snag bears N.44½°W., 28.8 ft. (Record, 29.04 ft.) with well healed single blaze.
Blaze pitched over.

23" Fir stump bears S.22½°W., 69.9 ft. Cut low.
No scribing visible.

Left cap in position.

New BTs - 12" D.Fir bears S.39°E., 47.65 ft. scribed "W 1/16 S29 CS BT" in double blaze.

9" Incense Cedar bears N.7½°E., 25.6 ft. scribed
"W 1/16 S20 CS BT" in double blaze.

Fd. OK, brass cap & 4 BTs. - Bureau of Land Management Resurvey - Jelley & Rogers, 1982 (DCSO records, Volume 45 Page 17524)