

PRIMARY CORNER DESCRIPTION W 1/16 Cor. for Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 8, 1957 and July 15, 1958 - (DCSO records, Volume 29 Page 12320)

Set an iron post 28" long 2½" dia. 24" in the ground, with brass cap marked:

S 1/16 S 8
 S 17
 1957

from which

A Madrone 8" dia. bears N.59½°E., 39 lks. dist. marked W 1/16 S8 BT.

A Fir 18" dia. bears S.40½°W., 114 lks. dist. marked W 1/16 S17 BT.

Doug. Co. Surveyors Office - V. Tracy; J. Barnett; M. Darby Jan/Feb. 1965 - C.S. File 53/47-14

Found - BLM brass cap and one live BT.
8" now 10" Laurel, N.59½°E., 25.7 ft. shows scribe on partially healed scar.
18" now 22" Fir S.40½°W., 75.2 ft. now stump, scribe marks visible on partially healed scar.
New BT - 5" W.Oak S.26°W., 62.4 ft. mkd: W 1/16 S17 CS BT.
This cor. lies on top of small spur between two small creeks.

BLM dependent resurvey by Wayne L. Rogers, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1755 surveyed June/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19902)

The W 1/16 sec. cor. of secs. 8 & 17, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of BTs by Zirpel, Roseberry, & Corbin
A madrone, 16" dia., bears N.57½°E., 37 lks., with healed blaze. (Record, N.59½°E., 39 lks.)

A sawed decayed fir stump, 22" dia., bears S.39½°W., 114 lks., with fragmentary scribe marks visible on partially healed decayed blaze. (Record, S.40½° W.)

and the remains of BTs mkd. by Tracy, in 1965

A decayed oak stump, 11" dia., bears S.27¾°W., 94 lks., no marks visible.

and a new bearing tree

A fir, 6" dia. bears S.21¼°W., 21 lks. mkd. W1/16 S17 BT

The corner is located S.45°E., 0.06 chs. of a fence corner, with woven wire fences extending N.70°E., S.70°W., and SE.

continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 220500

PRIMARY CORNER DESCRIPTION W 1/16 Secs 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2748, surveyed July 2014 - (DCSO records Vol. 58 Page 23174 & Plat 25-4 2015-1a&b)

The W 1/16 sec. cor. of secs. 8 & 17, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remaining bearing tree mkd. by Zirpel, Roseberry, and Corbin in 1957-58

A madrone, 13" dia., bears N.57¼°E., 24.4 ft., with a healed blaze.
and a new bearing tree

A fir, 16" dia., bears N.77½°W., 6.4 ft., mkd. W1/16 S8 BT.