

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1871
(DCSO records, Volume 9 Page 3759)

Set ¼ sec. post, from which
A Cedar 14" dia. bears S.40°E., 23 lks. dist.
A Fir 12" dia. bears N.35°E., 32 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 (DCSO records, Volume 29 Page 12305)

The cor. determined at record distance from two original
bearing trees, as follows:

A Fir 34" dia. bears N.39¼°E., 32 lks. dist. marked
with a healed blaze. (rec. bearing N.35°E.)
A Cedar 31" dia. bears S.40°E., 23 lks. dist. marked
with a healed blaze.

At the corner point, set an iron post, 28" long 2½" dia., 26"
in the ground, with brass cap marked:

T25S R4W
¼ S 29
S 32
1957

Bureau of Land Management Dependent Resurvey - Rogers and
Jelley - Group #1084, Survey Jan/June 1982 (DCSO records,
Volume 45 Page 17519)

Found - 1957 BLM brass cap projecting 3" above ground.
A Fir snag 35" dia. bears n.39¼°E., 32 lks. dist.
with healed blaze. Orig. BT.
A root hole bears S.40°W., 23 lks. dist. with an
uprooted cedar alongside, 33" dia. with healed
blaze. (Rec. S.40°E.) Original BT.
New BT - A Madrone 5" dia. bears S.40¼°W., 13½ lks. mkd ¼ S32
BT in the bark.
No other suitable trees available.

FD. Ok by K. Hoffine 4/2008 - M146-75