TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records Volume 9 Page 3740)

Set ¼ sec. post, from which
An Ash 8" dia. bears N.64°E., 114 lks. dist.
A Fir 40" dia. bears S.27°E., 136 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 1957 and July 1958 (DCSO records, Volume 29 Page 12320)

Point for corner, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long 2½" dia., 24" in the ground, with brass cap marked: T25S R4W
¼ S 8
S 17
1957 from which
A Fir 24" dia. bears N.65°W., 650½ lks.,mkd: ¼ S8 BT.
A Maple 16" dia. bears S.61°W., 183½ lks. mkd: ¼ S17 BT.
Corner falls on N. bank of fish pond, 60 lks. wide, 2 ft. deep, center bears south, 43 lks. dist.

BLM dependent resurvey by Wayne L. Rogers, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1755 surveyed June/Oct. 1995 - (DCSO records Vol. 52 Page(s) 19901)

From the ¼ sec. cor. of secs. 8 & 17, monumented with an iron post, 2½" diam., firmly set flush with the ground, with brass cap mkd. T25S R4W
¼ S8
S17
1957
from which the remains of BTs mkd. by Zirpel, Roseberry, & Corbin
A maple, 27" diam. bears S 61 W., 183½ lks. w/healed blaze
A decayed fir stump, 23" diam., bears N.65 3/4°W., 650½ lks.. with fragmentary scribe marks visible on decayed blaze. (Rec. N.65°W.)
and new accessories
The most southerly pole of two power poles, No. 1329, 14" diam., bears S.72½ E., 259 lks.
A stainless steel post, 28" long, 2½" diam., set 27" in the ground, for a reference monument, bears N.5°W., 27.3 lks., with brass cap mkd. RM 1/4 S8 18.0 FT. TO COR. 1995 & an arrow pointing to the corner. This monument is set in a woven wire fence, extending NE. and SW.