

PRIMARY CORNER DESCRIPTION Sec cor for 28, 29, 32 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records, Volume 9 Page 3753-4)

-----  
Set post cor. of secs. 28, 29, 32 and 33, from which  
A Fir 15" dia. bears S.7°E., 270 lks. dist.  
A Redwood 8" dia. bears S.4°W., 269 lks. dist.  
A Fir 50" dia. bears N.81°W., 350 lks. dist.  
A Fir 3" dia. bears N.63°E., 551 lks. dist.

Subdivisions of T25-4 as surveyed by W. H. Byars, Contract  
#152 dated June 1871. (DCSO records, Volume 9 Page 3757)

-----  
Set post cor. to secs. 28, 29, 32 and 33, from which  
A Fir 4" dia. bears N.60°E., 30 lks. dist.  
A Fir 10" dia. bears S.30°E., 300 lks. dist.  
A Fir 16" dia. bears S.10°W., 300 lks. dist.  
A Fir 16" dia. bears N.75°W., 500 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin  
and Roseberry. Special Instructions dated July 8, 1957 and  
July 15, 1958 (DCSO records, Volume 29 Page 12296)

-----  
Corner determined at record distances from two remaining  
original bearing trees, as follows:  
A burned and rotted Fir snag, 31" dia. bears N.72½°E., 30  
lks. dist., with illegible scribe marks on 4" core  
in center of tree. (Rec. bearing, N.60°E.)  
A sawed Fir stump 40" dia. bears S.17°W., 300 lks. dist.  
with scribe mark S visible on burned & opened blaze.  
(Record bearing, S.10°W.)

At the corner point, set an iron post 28" long, 2½" dia. 26"  
in the ground, with brass cap marked:

T25S R4W  
S 29 | S 28  
S 32 | S 33

1957 from which

A Fir 24" dia. bears N.48°45'E., 195 lks. dist. marked  
T25S R4W S28 BT.  
A Cedar 25" dia. bears S.57½°E., 164 lks. dist. marked  
T25S R4W S33 BT.  
A Fir 17" dia. bears S.37°W., 142 lks. dist. marked  
T25S R4W S32 BT.  
A Fir 7" dia. bears N.64¼°W., 214 lks. dist. marked  
T225S R4W S29 BT.

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Doug. Co. Surveyors Office - Vernon Tracy; M. Darby; J. Barnett - Feb/March 1965 - C.S. File 53/47-63  
-----

Found - 1957 BLM brass cap and two live BTs:  
25" now 25" Cedar S.57½°E., 108.2 ft., shows "T25S R4W S33 BT" on partially healed blaze.  
7" now 10" Fir N.64¼°W., 141.2 ft. face pitched over  
Did not open.  
Other BTs burned out and out of place.  
New BTs - 9" D.Fir N.40°E., 6.4 ft. mkd: T25S R4W S28 CS BT.  
8" D.Fir S.71°W., 29.0 ft. mkd: T25S R4W S32 CS BT.  
This corner lies on very steep south slope 25.0 ft. south of E-W fence.

BLM Dependent Resurvey - Jelley & Rogers, Group #1084 - Survey, Jan/June 1982 (DCSO records Volume 45 Page 17516-17)  
-----

Found - 1957 BLM brass cap  
Orig. BT, a Fir rootcrown 30" dia. bears N.72½°E., 30 lks., no marks remain.  
Orig. BT, a Fir rootcrown 40" dia. bears S.17°W., 300 lks., no marks remain.  
1957 BT, A Cedar 30" dia. bears S.57½°E., 164 lks. with scribe marks T25S R4W S33 BT visible on open blaze  
1957 BT, A root hole, bears S.37°W., 132 lks. dist. with an uprooted Fir alongside, 20" dia., no marks visible (Record, 142 lks.)  
1957 BT, A root hole, bears N.64¼°W., 214 lks. dist. with an uprooted Fir alongside, 10" dia., with fragmentary scribe marks visible on open blaze.  
New BTs - A Fir 16" dia. bears N.85°E., 252 lks. mkd. T25S R4W S28 BT.  
A Cedar 10" dia. bears S.51°W., 355 lks. mkd T25S R4W S32 BT.  
An Oak 11" dia. bears N.86½°W., 534 lks. mkd. T25S R4W S29 BT.

FD. Ok by K. Hoffine 4/2008 - M146-75

continued next page

PRIMARY CORNER DESCRIPTION Sec. cor. for 28, 29, 32 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by A. Bert Skeesick & Timothy J. Moore, Cadastral Surveyors and Robert H. Browning, Surveying Technician under Group No. 2069 - Surveyed Feb./March 2004 - (DCSO records Vol. 55 Page(s) 21565-6)

-----  
The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½" dia., firmly set, projecting 5 ins. above ground, with brass cap (properly) mkd

from which the remaining BT by Zirpel, Roseberry and Corbin  
A cedar, 33" dia., bears S.57½°E., 108.2 ft., with fragmentary scribe marks visible on a burned partially healed blaze.

and bearing trees mkd. by Jelley and Rogers

A fir, 23" dia., bears N.84°E., 166.3 ft., with fragmentary scribe marks visible on a burned partially healed blaze. (Record, N.85°E.)

A cedar, 19" dia bears S.51°W 234.3 ft with a healed blaze

An oak, 13" dia., bears N.86½°W., 352.4 ft., with fragmentary scribe marks visible on a partially healed blaze.

Corner lies 33 ft. N. of down wire fence, bears N.80°W. and S.80°E.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 28, 29, 32, and 33, T. 25 S., R. 4 W., as determined from a tie to Geodetic Control Station EC41298, established by the(BLM) in 2004 is as follows:

Latitude: 43°21'34.79"N.

Longitude: 123°11'11.61"W.

From this corner, BLM Geodetic Control Station "EC 41298", at latitude 43°19'41.328"N. and longitude 123°11'32.087"W., determined by the NAVSTAR GPS utilizing static, dual frequency carrier phase receivers, bears S.7°30'15"W., 11587.44 ft.(mean bearing and sea level dist.), monumented with an aluminum rod, 3/4" dia., firmly set, flush with the ground, with aluminum cap mkd. EC41298 GPS 2004.