TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars under Contract #152 dated June 1871 (DCSO records, Volume 9 Page 3757)

Set ¼ sec. post, from which
A Fir 14" dia. bears N.2°W., 40 lks. dist.
A Fir 15" dia. bears N.2°E., 55 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 8, 1957 and July 15, 1958 - (DCSO records, Volume 29 Page 12297)

Corner determined at record distance from the original bearing trees, as follows:
A Fir 27" dia. bears N.5¼°E., 55 lks. dist., with a healed blaze. (Rec. bearing N.2°E.)
A stump hole of a down Fir, 18" dia. bears N.9½°W., 40 lks. dist.; the Fir lies downhill from the stump hole & has scribe marks ¼ S visible on opened blaze. (Record bearing N.2°W.)
At the corner point, set an iron post, 28" long 2½" dia., 26" in the ground, with brass cap marked: T25S R4W

¼
S 29|S 28
1957

from which
A Fir 30" dia. bears N.78½E., 45 lks. mkd ¼ S28 BT.
A Fir 37" dia. bears N.16½°W., 52 lks. mkd ¼ S29 BT.

Bureau of Land Management Dependent Resurvey - Rogers and Jelley - Group #1084, Survey, Jan/June 1982 - (DCSO records, Volume 45 Page 17518)

Found - 1957 BLM brass cap projecting 3" above ground.
Orig. BT, a sawed Fir stump 29" dia. bears N.5¼°E., 55 lks., no marks visible.
1957 BT, a Fir snag 33" dia. bears N.78½°E., 45 lks. with scribe marks ¼ S28 visible on open blaze.
New BTs - A Cedar 25" dia. bears N.5°E., 50 lks. mkd ¼ S 28 BT
A Fir 15" dia. bears S.74¼°W., 248 lks. mkd ¼ S29 BT

FD. Ok by K. Hoffine 4/2008 - M146-75