

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3741)

Set post cor. of secs. 20, 21, 28 and 29, from which
A Fir 6" dia. bears S.18°E., 28 lks. dist.
A Fir 10" dia. bears S.60°W., 68 lks. dist.
A Fir 10" dia. bears N.60°W., 93 lks. dist.
A Willow 3" dia. bears N.43°E., 15 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - Survey, Jan/June 1982 (DCSO records, Volume
29 Page 12298)

Corner determined at record bearing and distance from the only
remaining original bearing tree as follows:

A Fir, dead and down, 14" dia. bears N.60°W., 93 lks.
dist., with scribe mark S visible in a burned and
opened blaze.

At the corner point, set an iron post, 28" long, 2½" dia., 26"
in the ground, with brass cap marked:

T25S R4W
S 20 | S 21
S 29 | S 28

1957 from which

A Fir 6" dia. bears N.85°E., 27 lks. mkd T25S R4W S21 BT
A Fir 6" dia. bears S.74°E., 42 lks. mkd T25S R4W S28 BT
A Madrone 8" dia bears S.19½°W. 60 lks mkd T25S R4W S29BT
A Fir 5" dia. bears N.60°W., 84½ lks. mkd T25S R4W S20 BT

From this point, a locally established corner of secs. 20, 21,
28 and 29 bears S.60°E., 23½ lks., monumented with a ½" iron
bar, 3" above ground, firmly set, in a fence corner with
fences extending N. and S. from which

A Fir 4" dia. bears N.45°E., 19 lks. mkd S21 BT on a
partially healed blaze.

A Fir 6" dia. bears S.57¼°E., 33 lks. mkd S28 BT on a
partially healed blaze.

A Fir 6" dia. bears S.42°W., 29 lks. mkd S29 BT on a
partially healed blaze.

A Madrone 9" dia. bears N.5°45'W., 35½ lks. mkd S20 BT.

FD. Ok by K. Hoffine 4/2008 - M146-75