



TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 28" diam., bears N.32°E., 118½ lks., with healed blaze. (Record, N.33°E.)

A fir, 16" diam., bears S.29°W., 62 lks., with healed blaze. (Record, S.30¼°W.)

From this point, a point established as the ¼ sec. cor. of secs. 16 & 17 by proportionate measurement by Irving, in 1939, recorded in the Douglas County Surveyors Office map file M5-66, bears S.85°22'02"E., 0.201 chs. dist.; monumented with an iron pipe, 3/4" diam., firmly set, projecting 4" above ground. This point is erroneously positioned and is not utilized in this survey.

From this same point, the BLM Geodetic Control Station No. EC41231, at latitude 43° 23' 40.991" N., longitude 123° 11' 29.505" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S.76°27'11"W., 21.582 chs. (mean bearing & sea level distance); monumented with an aluminum cap, 3½" diam., firmly set flush with the ground, with top mkd. EC41231 GPS 1994, from which an orange carsonite survey marker bears N., 5 ft. dist.