

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec Cor for 4 & 5; 32 & 33 of T24-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
(DCSO records, Volume 7 Page 3027)

-----  
Set post cor. of secs. 4,5, 32 and 33, from which  
A W.Oak 24" dia. bears S.53½°W., 195 lks. dist.  
A W.Oak 18" dia. bears N.38¼°W., 84 lks. dist.  
A W.oak 36" dia. bears S.54½°E., 332 lks. dist.  
A W.Oak 10" dia. bears N.86¼°E., 119 lks. dist.

Milo E. Godfrey, Deputy - V. Tracy; M. Stone - May 10, 1963  
C.S. File 53/9-79

-----  
Found - 28" rotted Oak stump S.53½°W., 128.7 ft. No scribe  
marks.  
28" W.Oak N.38½°W., 55.4 ft. Chopped it open and  
found scribing.  
48" W.Oak S.54½°E., 219.1 ft. shows good scar.  
No trace of other bearing trees.  
1" Iron rod and a sandstone 9"x16"x6" at corner.  
Set brass cap at cor. mkd: County Surveyor's T24-4 S32|S33  
Office, 1963 S 5|S 4  
New BTs - 7" W.Oak N.60°E., 19.0 ft. mkd: T24S R4W S33 CS BT.  
9" D.Fir N.24°W., 55.2 ft. mkd: T24S R4W S32 CS BT.  
7" D.Fir S.14°E., 46.5 ft. mkd: T25S R4W S4 CS BT.  
5" W.Oak S.41½°W., 28.7 ft. mkd: T25S R4W S5 CS BT.

Found OK, D. Peel, August 1992 - M 115 - 62  
Found OK, H. Christensen - Dec 1995 - M 123-25 A&B