TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1871
(DCSO records, Volume 9 Page 3757)

Set ¼ sec. post, from which
A Fir 16" dia. bears S.50°E., 29 lks. dist.
A Fir 5" dia. bears N.40°W., 40 lks. dist.

Doug. Co. Surveyors Office - Vernon Tracy; M. Darby; J. Barnett - May 26, 1966 - C.S. File 53/47-9

Found - Orig. 16" now 22" Fir snag S.50°E., 19.1 ft. upper scar previously opened & shows fragmentary scribe, chop out lower scar & find "T"., also scribe on ground at base of tree.
No trace of other original bearing tree.
Set brass cap mkd: County Surveyors T25S R4W ¼ S 28 / S 33
County, 1966
New BTs - 11" W.Fir S.51°W., 9.7 ft. mkd: ¼ S33 CS BT.
9" D.Fir N.70°W., 11.2 ft. mkd: ¼ S28 CS BT.
Corner lies approx. 150 ft. East of creek, course North.

Fd. Ok by K. Hoffine 4/2008 - M146-75

BLM Dependent resurvey by A. Bert Skeesick & Timothy J. Moore, Cadastral Surveyors and Robert H. Browning, Surveying Technician under Group No. 2069 - Surveyed Feb./March 2004 - (DCSO records Vol. 55 Page(s) 21563-4)

The 1/4 sec. cor. of secs. 28 and 33, perpetuated by the Douglas County Surveyors Office in 1966, monumented with an iron post, 1¼" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A decayed fir stump, size indeterminate, bears S.50°E., 19.1 ft., with axe marks visible.
and bearing trees mkd. by the Douglas County Surveyors Office
A fir, 22" dia., bears S.49¾°W., 9.8 ft., with a healed double blaze.
A fir, 17" dia., bears N.69°W., 11.2 ft., with a healed double blaze.
and bearing tree mkd. by persons unknown
A fir, 40" dia. bears S.76¼°W. 33.2 ft. mkd. ¼ in the bark