TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855 (DCSO records, Volume 9 Page 3752-3)

Set ¼ sec. post, from which
A Cedar 24" dia. bears S.7°E., 39 lks. dist.
A Fir 12" dia. bears N.82°W., 4 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 8, 1957 and July 15, 1958 (DCSO records, Volume 29 Page 12290)

Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked: T25S R4W

¼
S 28 | S 27
1957

from which
A W.Fir 9" dia. bears S.20°E., 98 lks. dist. mkd. ¼S27BT.
A W.Fir 7" dia. bears N.89°W., 7 lks. dist. mkd. ¼ S28BT.

Doug. Co. Surveyors Office - V. Tracy; M. Darby; J. Barnett January, 1965 - C.S. File 53/47-33

Found - 1957 BLM brass cap and BTs as follows:
9" now 11" W.Fir S.20°E., 64.7 ft. partially grown over. We do not open.
7" now 7" W.Fir snag, N.89°W., 4.6 ft., shows "¼ S28 BT" scribe.
New BT - 15" Yew, S.44°W., 31.9 ft. mkd: ¼ S28 CS BT.

FD. 1957 brass cap and 2 BTs. BLM Dependent Resurvey, 1983 Rogers & Bishop - (DCSO records, Volume 46 page 17773)

FD. Ok by K. Hoffine 4/2008 - M146-75