

PRIMARY CORNER DESCRIPTION N. 1/16 Cor. Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 7, 1957 and July 15, 1958 - (DCSO records, Volume 29 Page 12291)

-----  
At point for the N 1/16 sec. cor. of secs. 27 and 28,  
Set an iron post, 28" long 2½" dia. 24" in the ground, with  
brass cap marked:

N 1/16  
S 28|S 27

1957

from which

A W.Fir 10" dia. bears S.89°E., 24 lks. dist. marked  
N 1/16 S27 BT.

A W.Fir 10" dia. bears S.68°W., 29 lks. dist. marked  
N 1/16 S28 BT.

Doug. Co. Surveyors Office - Vernon Tracy; Mike Darby; Jack Barnett - Jan/Feb. 1965 - C.S. File 53/47-12

-----  
Found - 10" now 12" D.Fir S.68°W., 19.1 ft. recorded as W.  
Fir, partially grown over scar, we find  
scribing.

BLM brass cap & other BT destroyed by slide in small  
creek.

The BT found, does not appear to have been affected by slide.  
Because of the possibility of continued sliding in the  
immediate area, we set: WITNESS CORNER 32.0 ft. South.

Set - WIT. COR. brass cap marked: County Surveyors Office  
1965 T25S R4W W.C. 32 ft. N. to N. 1/16 S28|S27

New BTs - 24" Cedar S.56°E., 20.9 ft. mkd: W.C. N. 1/16 S27  
CS BT.

6" D.Fir S.87°W., 25.2 ft. mkd: W.C. N. 1/16 S28  
CS BT.

Bureau of Land Management Dependent Resurvey - Bishop and Rogers, Group #1161, Survey July/Sept. 1983 (DCSO records, Volume 46 Page 17774)

-----  
Point for the N 1/16 sec. cor. of secs. 27 and 28 determined  
at record bearing and distance from the remaining bearing tree  
marked by Zirpel, Roseberry and Corbin:

A Fir 16" dia. bears S.68°W., 29 lks. dist. with a healed  
blaze.

(Continued Next page)

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 400260

PRIMARY CORNER DESCRIPTION N 1/16 Cor. for Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

At the corner point, set an iron post, 28" long, 2½" dia., 26"  
in the ground, with brass cap marked:     N 1/16  
  S 28|S 27  
  1983

From which a new bearing tree:

    A Fir 9" dia. bears N.10½°E., 39 lks. dist. marked  
        N 1/16 S27 BT.

From this point, a point established and recorded by Vernon  
R. Tracy, Deputy Co. Surveyor, in 1965, bears South, 0.485  
chs. dist., monumented with an iron pipe, 1¼" dia., firmly set  
projecting 6" above the ground, with brass cap mkd. WC T25S  
R4W 32 Ft N to N 1/16 S 27 S28 1965, from which the remains  
of the bearing trees mkd. by Tracy:

    A Cedar stump 32" dia. bears S.56°E., 31 lks. dist. with  
        a healed double blaze.

    A Fir 8" dia. bears S.87°W., 39 lks. dist. with a healed  
        double blaze.