

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3747)

Set post cor. of secs. 9, 10, 15 and 16, from which
Erected mound, drove charred stake.
Dug ditch with pits as per instructions.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 7, 1957 and
July 15, 1958 (DCSO records, Volume 29 Page 12294-95)

Point for the cor. of secs. 9, 10, 15 and 16, in field, at
proportionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28" long 2½" dia. 48" in the ground, with
brass cap marked:

T25S R4W
S 9 | S 10
S 16 | S 15

1957 from which

A Cedar 14" dia. bears N.43°45'E., 322½ lks. dist., mkd.
T25S R4W S10 BT.

A Pear 6" dia. bears S.56°45'E., 311 lks. dist., marked
T25S R4W S15 BT. located in fence row.

A Power and telephone pole, 12" dia. bears S.70¼°W., 702
lks. dist. with number 3H5-6 on metal tag.

A Power and telephone pole, 12" dia. bears N.70¼°W.,
897 lks. dist. with # 3H5-5 on metal tag.

A Cedar post, cor. of fences extending N. and E. bears
N.22°35'E., 27 lks. dist., marked X BO.

Found OK, August 1992, D. Peel - M 115 - 62

Douglas Co. Surveyors Office -Randall W. Smith - John Pike -
12/23/97 - C.S. File 64/78-42

Found - Brass cap on an iron pipe 16" below ground, unable
to read stamping. 1958

A metal fence post is along S'ly edge of BC/IP.
Cedar corner post with fencing running North and
East has fallen over near the rec. position
(N.22°35'E., 17.8 ft.) 1958

Power pole with scribing "X BO" bears S.70¼°W.,
462.6 ft. (Rec. S.70¼°W., 463.3 ft.) 1958

Cont. next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

592.0 Power pole with scribing "X BO" bears N.70¼°W.,
ft. (agrees with rec.) 1958

New BTs- Double trunked W.Oak double blazed and scribed "T25S
R4W S15 CS BT" on 16" dia., Northerly trunk,
center of root crown, bears S.52°E., 445.1 ft.

16" W.Oak double blazed and scribed "T25S R4W S9 CS
BT" bears N.4½°W., 36.6 ft.

8" Pear double blazed and scribed "X BT" bears
N.59½°E., 179.9 ft.

17" Cedar double blazed and scribed "T25S R4W S10 CS
BT", bears N.85°E., 173.6 ft.

Found OK by N. Hibbs, Oct. 2002 - M141-15