

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3748)

Set post cor. of secs. 3, 4, 9 and 10, from which
A W.Oak 10" dia. bears N.82°E. 56 lks. dist.
A W.Oak 18" dia. bears S.76°E., 77 lks. dist.
A B.Oak 15" dia. bears S.4°W., 152 lks. dist.
A Fir 24" dia. bears N.23°W., 700 lks. dist.

O.F. Thiel - For: Eliza Rone - 7/1930 (Recorded 8/31/1998) -
F.B. 116 Pg. 46

Old post and stone for corner, marked new trees:
Fir, 30" S.7°E., 25 (lks)
Fir, 32" S.79°W., 22.5 (lks)
Fir, 20" N.11°W., 16 (lks)
Fir, 12" N.57°E., 13.5 (lks)

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 (DCSO records, Volume 29 Page 12295)

Found Corner perpetuated by an iron pipe, 3 ft. long, 1" dia.
firmly set 21" in the ground, from which the remains of the
original bearing tree:

A rotted and uprooted B.Oak bears S.4°W., 152 lks. dist.
no marks remaining.
and trees marked by local surveyors: (Not of record)
A rotted and burned fir snag, 10" dia. bears N.57½°E.,
13½ lks. dist. with scribe marks S3 visible on
burned blaze.
A burned fir snag, 24" dia. bears S.5½°E., 27 lks. dist.
with scribe marks T25S R4W S10 BT visible on burned
blaze.
A burned fir snag 25" dia. bears S.76°45'W., 24 lks.
dist.; no marks remaining on burned blaze.
A rotted and burned Fir stump 18" dia. bears N.12½°W.,
17 lks. dist., no marks remaining on lower portion
of burned blaze.

At the corner point, set an iron post, 28" long, 2½" dia., 24"
in the ground, with brass cap marked: T25S R4W

S 4 | S 3
S 9 | S 10

1957 from which

A Fir 9" dia. bears N.78¼°E., 60½ lks. dist. marked
T25S R4W S3 BT.

(Cont. next page)

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 20" dia. bears S.31°E., 277 lks. dist., marked
T25S R4W S10 BT.
A Fir 7" dia. bears S.57½°W., 55½ lks. dist., marked
T25S R4W S9 BT.
A Fir 8" dia. bears N.12½°W., 53½ lks. dist. marked
T25S R4W S4 BT.
Reset iron pipe alongside iron post.

Found OK, August 1992, D. Peel - M 115 - 62
Found OK, DEC. 1995, H. Christensen - M 123-25 A&B
Found OK by N. Hibbs, Oct. 2002 - M141-15