

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 420300

PRIMARY CORNER DESCRIPTION W 1/16 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin and Roseberry - Special Instructions dated July 8, 1957 and July 15, 1958 (DCSO Records, Volume 29 Page 12293)

At point for the W 1/16 sec. cor. of secs. 22 and 27,
Set an iron post 28" long, 2½" dia. 26" in the ground, with
brass cap marked: S 22

W 1/16 S 27
1957 from which
A Fir 9" dia. bears N.2½°W., 57 lks. dist. marked
W 1/16 S22 BT.
A Cedar 15" dia. bears S.6°W., 27 lks. dist. marked
W 1/16 S27 BT.

Douglas Co. Surveyor Office - Vernon Tracy; Mike Darby; Jack Barnett - Jan/Feb. 1965 - C.S. File 53/47-7

Found - BLM brass cap set in 1957 and both BTs, now snags:
9" Fir, now 11" N.2½°W., 37.6 ft., shows faint
scribe on burned face.
15" now 15" Cedar, S.6°W., 17.8 ft. ace badly burned
no scribe visible. Rescribe Cedar "W 1/16 S27
CS BT.

New BTs - 12" Madrone N.1°W., 90.5 ft. mkd: W 1/16 S22 CS BT.
12" Madrone S.87°E., 97.3 ft. mkd: W 1/16 S27 CSBT.

Fd. brass cap and 3 BTs. BLM Dependent Resurvey, 1983, Rogers and Bishop, Group #1161 - (DCSO records, Vol. 46 Pg. 17776-77)