TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3; & 34 of T24-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 7 Page 3028)

Set ¼ sec. post, from which
A Laurel, 3" dia. bears N.30°W., 59 lks. dist.
A Fir 8" dia. bears S.11°E., 257 lks. dist.

James W. Byron, Deputy - Clete Putnam - July 10, 1961
C.S. File 49/124-24

Found - Old scribed stake at corner & orig. 8" now 40" Fir, S.11°E., 169.4 ft. Opened several years ago, shows orig. scribing "¼" & rescribing "¼"
Orig. West BT not found.
Set brass cap at cor. mkd: County Surveyor's ¼ S34 T24S Office, 1961 S 3 T25S
Corner in East-West fence line.
New BTs - 14" R.Fir bears S.43°W., 4.5 ft. scribed ¼ S3 CSBT.
18" R.Fir (in fence line scribed above fence) bears N.43°E., 3.0 ft. scribed ¼ S34 CS BT.

Fd. Ok by H.Christensen, Dec. 1995 - M123-21