

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June, 1871
(DCSO records, Volume 9, Page 3764)

Set post cor. to secs. 26, 27, 34 and 35, from which
A cedar 30" dia. bears N.55°E., 6 lks. dist.
A Fir 8" dia. bears S.25°E., 48 lks. dist.
A Fir 24" dia. bears S.12°W., 34 lks. dist.
A Fir 6" dia. bears N.45°W., 22 lks. dist.

James W. Byron, Deputy Co. Surveyor - For: Wilbur Lbr. Co.
November, 1955 - C.S. File 47/44 and M 2-1

Corner reset by double proportion measurement, using ¼ cor.
to North, ¼ cor. to South, ¼ cor. to West and Sec. cor. to
Secs. 25, 26, 35 and 36.

Set brass cap mkd: 26 27 T 25, R 4 W, Co. Su. Office 1955.
34 35

Blazed and scribed:

60" Cedar N.36°08'E., 265.19 ft. mkd. S 26 C.S.B.T.
6" Laurel, N.58°47'E., 59.84 ft. mkd. S 26 C.S.B.T.
5" Laurel S.18°24'30"E., 15 ft. mkd. S 35 C.S.B.T.
No trees near in SW or NW quad.

Bureau of Land Management Dependent Resurvey - Zirpel; Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 (DCSO records, Volume 29 Page 12278-79)

Found - 1955 County brass cap.
60" Cedar bears N.32¼°E., 401 lks. dist. mkd.
T25S R4W S26 CS BT on a partially healed blaze
6" madrone bears N.56¼°E., 94 lks. dist. mkd. S26
CS BT on a partially healed blaze.
5" madrone bears S.29¼°E., 27 lks. dist. marked S35
CS BT on a partially healed blaze.

At the corner point, set an iron post, 28" long 2½" dia. 26"
in the ground, with brass cap marked:

T25S R4W
S 27 | S 26
S 34 | S 35
1957

from which

A Cedar 20" dia. bears N.60½°E., 365 lks. dist. marked
T25S R4W S26 BT.

A Madrone 8" dia. bears S.35¼°E., 176 lks. dist. marked
T25S R4W S35 BT.

(Continued Next Page)

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 38" dia. bears S.50°W., 468 lks. dist. marked
T25S R4W S34 BT.
A Fir 48" dia. bears W.; 406 lks. dist. marked T25S
R4W S34 BT.
Deposit county surveyor's post alongside iron post.

2