

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1971
(DCSO records, Volume 9 Page 3766)

Set post cor. to secs. 22, 23, 26 and 27, from which
A Fir 10" dia. bears N.40°E., 7 lks. dist.
A Fir 14" dia. bears S.30°E., 35 lks. dist.
A Fir 12" dia. bears S.50°W., 36 lks. dist.
A Cedar 10" dia. bears N.12°W., 20 lks. dist.

Bureau of Land Management Dependent Resurvey - Zirpel, Corbin
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - (DCSO records, Volume 29 Page 12281-82)

The cor. of secs. 22, 23, 26 and 27, determined at record
bearing and distance from the only remaining orig. BT,
A dead Hemlock 21" dia. bears S.50°W., 36 lks. dist.
with scribe marks 7 5 BT visible on a partially
opened and rotted blaze. (Record calls for a Fir BT)
At the corner point, set an iron post, 28" long 2½" dia. 26"
in the ground, with brass cap marked: T25S R4W
S 22 | S 23
S 27 | S 26
1957 from which

A Yew 8" dia. bears N.66½°E., 66 lks. dist. marked
T25S R4W S23 BT.
A Cedar 9" dia. bears S.50¼°E., 90 lks. dist. marked
T25S R4W S26 BT.
A Maple 11" dia. bears S.45¼°W., 97 lks. dist. marked
T25S R4W S27 BT.
A Hemlock 18" dia. bears N.53½°W., 65 lks. dist. marked
T25S R4W S22 BT.

Bureau of Land Management Dependent Resurvey - Bishop and
Rogers, Group #1161 - Survey, July-Sept. 1983 - (DCSO records,
Volume 46 Page 17766)

Found - 1957 BLM brass cap.
Yew 14" dia. bears N.66½°E., 66 lks. with healed
blaze.
Cedar 19" dia. bears S.50¼°E., 90 lks. dist. with
healed blaze.
Maple 14" dia. bears S.45¼°W., 97 lks. dist. with
scribe marks R4W S27 visible on partially
healed blaze. (Cont. next Page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Hemlock 19" dia. bears N.53½°W., 65 lks. dist.
with scribe marks R4W S22 BT visible on
partially healed blaze.
and a new bearing tree:
A Cedar 3" dia. bears S.29°W., 52 lks. dist. mkd.
X BT.
The corner is located at the end of a fence line extending N.