

PRIMARY CORNER DESCRIPTION CW 1/16 Sec. 2

Alias	Description

Douglas Co. Surveyors Office - Frank Cain, Co. Surveyor - May 1914 - For: Hunt, Manning & Abeene - Old Vol. 2 Pgs 256-257

Set 1/16 cor. from which
 A cedar 20" dia., bears N.89½°E., 393 lks.
 A W.Oak 12" dia., bears S.70¾°W., 345 LKS.

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Mike Koch - 4/15/2016 - C.S. File 67/44-7

Found - No monument fd.
BTs by Cain in 1914 -
 A 38" dia. x 5 ft. tall cedar stump bears N.89½°E., 259.4 ft. which is opened to reveal an axe notch and a blazed face with an intact scribed "6" and several other illegible scribe marks visible. (Rec. N.89½°E., 393 lks.)
Set - At a point S.89½°W., 259.4 ft. from the above described original bearing tree, I set a 5/8" x 30" iron rod 27" in the ground with a 1½" dia. aluminum cap marked: DOUGLAS CO. SURVEYOR 2016
New - An 18" double trunk W.Oak bears N.02°E., 200.0 ft. scribed "CW 1/16 S2 CS BT" on the southerly trunk.
 A 7" dia. I.Cedar bears N.49½°E., 105.1 ft. scribed "CW 1/16 S2 CS BT".
 A 3" dia. USGS brass disc marked "H 60 1934" set in the top of a 1½ ft. x 2 ft. x 2½ ft. rock outcrop bears S.23°50'00"E., 275.23 FT.
Compass declination 15°E.
Location & comments -
 Basis of bearings: N.89°48'28"W. 643.41' per PP 2008-0061F between 1968 CO. RD. NO. 19 R/W Monuments(sheet 3 of 9 = PG. 09931059) @ 35' LT. of 45+50 & 51+93.32. Equipment - NIKON DTM 520
All BTS have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown unless otherwise noted. Corner falls on a moderate south slope 1.6 ft. north of a partly fallen east-west wire fence line in open pasture land surrounded by mixed forest.