

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1871
(DCSO records, Volume 9 Page 3761)

Set post cor. to secs. 23, 24, 25 and 26, from which
A Fir 48" dia. bears N.1°E., 7 lks. dist.
A Fir 16" dia. bears S.70°E., 10 lks. dist.
A Cedar 16" dia. bears S.10°W., 23 lks. dist.
A Cedar 10" dia. bears N.70°W., 33 lks. dist.

Bureau of Land Management Dependent Resurvey - Corbin, Zirpel
and Roseberry - Special Instructions dated July 8, 1957 and
July 15, 1958 - (DCSO records, Volume 29 Page 12270)

Point for the cor. of secs. 23, 24, 25 and 26, at proportionate
distance; there is no remaining evidence of the original cor.
Set an iron post, 28" long, 2½" dia. 26" in the ground, with
brass cap marked:

T25S R4W
S 23 | S 24
S 26 | S 25

1957

from which

- A Madrone 6" dia. bears N.86°E., 44 lks. dist. marked
T25S R4W S24 BT.
- A Fir 7" dia. bears S.76°E., 32 lks. dist. marked
T25S R4W S25 Bt.
- A Madrone 9" dia. bears S.64°W., 14 lks. dist. marked
T25S R4W S26 BT.
- A Madrone 6" dia. bears N.50°W., 109 lks. dist. marked
T25S R4W S23 BT.

FD OK, K HOFFINE - 2/8/2007 - C.S. FILE 65/60-32