

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3744)

Set ¼ sec. post, from which
 An Oak 8" dia. bears S.63°W., 42 lks. dist.
 A W.Oak 10" dia. bears S.73°E., 40 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;
Royal Abeen; Av Abeen - Sept. 14, 1929 - C.S. File 37/5
Volume 3 Page 298; C.S. 36/58; Field Book 66

Location identified by down and rotten OBT, S.73°E., 20 lks.
bearing proper scribe marks. Also a Fir 24" dia. N.70°E., 29
lks. which had been marked by Surveyor Thiel many years ago
I reblaze and scribe ¼ S 12 CSBT Blaze and scribe New BT:
 A 24" Fir N.25°W., 125 lks. ¼ S. 11 CSBT.
Drove 1¼" car axle flush with ground for corner. Set a post
alongside mkd: ¼ S12 on the E face; ¼ S11 on the W. face; and
CS on the S face.

Vernon R. Tracy, Doug. Co. Surveyors Office - M. Darby; J.
Barnett - November 1964 - C.S. File 53/47-27

Found - 1¼" Iron axle shaft, as called for by Irving.
 Stump of one BT. No trace of other BT.
 24" now 30" D.Fir stump N.70°E., 19.1 ft. shows
 scar, we open & find burned face.
New BTs - 8" R.Cedar N.1°E., 5.6 ft. mkd: ¼ S12 CS BT.
 7" R.Cedar S.34°W., 37.5 ft. mkd: ¼ S11 CS BT.
This corner lies on E. edge of old cat road, 3.0 ft. north
of fence corner.

Fd. 1" Axle by Greg Lang - April 2002 - M139-73
Fd. Ok by Kris DeGroot - March 2003 - M137-57