TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 1, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3744)

Set post cor. of secs. 1, 2, 11 and 12, from which
An Ash, 6" dia. bears N.63°E., 27 lks. dist.
An Ash, 6" dia. bears S.39°E., 45 lks. dist.
An Ash 4" dia. bears N.55°W., 21 lks. dist.
A Redwood, 10" dia. bears S.74°W., 17 lks. dist.

C.E. Roberts - Survey for: J.S. Hunt - May 28, 1903
Field Book 7 Page 14

W.Oak 6" S.6°E., 15 lks.
Ash, 7" S.21°W., 17 lks.

Vernon R. Tracy, Douglas Co. Surveyors Office - M. Darby;
J. Barnett - November 1964 - C.S. File 53/47-59

Found - 6" now 12" W.Oak S.6°E., 9.9 ft. shows scar, did not open.
7" now 13" Ash S.21°W., 11.2 ft., open & find "S" scribe.

Set Brass cap at cor. mkd: County Surveyors T25S R4W Office, 1964

S 2	S 1
S11	S12

New BTs - 8" W.Oak N.8°W., 24.9 ft. mkd: T25S R4W S2 CS BT.
6" W.Oak N.36°E., 24.1 ft. mkd: T25S R4W S1 CSBT.

This corner lies 5 ft. South and 65 ft. West of fence corner, with fences running N. & E. on E. edge of old cat road.

Fd. Ok by Greg Lang - April 2002 - M139-73
Fd. Ok by Kris DeGroot - March 2003 - M137-57
FD. ok by Kris DeGroot, 8/2008 - 2008-0061A-G