TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Gordon & Gardner, Contract #52 dated Feb. 1855
(DCSO records, Volume 9 Page 3745)

Set ¼ sec. post, from which
A W.Oak 8" dia. bears S.56°W., 60 lks. dist.
A Fir 30" dia. bears N.57°E., 107 lks. dist.

F.J. Cole, for: Hunt, Manning and Abeene - May 4, 1914
Volume 2 Page 256 and F.B. 39 Page 34

Set stake N.56°E., 60 lks. from Oak BT.

Doug. Co. Surveyors Office - N.E. Richardson; E.S. Woodford
May 1945 (No source record found)

Renewed this corner from old bearing trees. Marked:
A 14" Fir N.36°00'W., 19.5 ft.
A 24" Fir S.68°30'E., 30.7 ft.
An 8" Oak S.56°00'W., 39.6 ft. Old BT, in good condition.

Milo Godfrey, Deputy County Surveyor - Vernon Tracy; Mike Stone - May & June 1963 - C.S. File 53/9-97

Found - 2" sq. wooden stake, still standing but rotten.
26" D.Fir S.68½°E., 30.7 ft. bark scribing visible "¼ S 1".
16" D.Fir N.36°W., 19.5 ft. Two good axe scars visible, did not open.
Down & rotten old Oak S.56°W., 39.6 ft. scribing visible, Orig. BT.
No trace of original NE bearing tree.
Set brass cap at cor. mkd: County Surveyor's Office, 1963
T25S R4W ¼ S2|S1
Rescribe - 26" D.Fir S.68½°E., 30.7 ft. mkd: ¼ S1 CS BT.
All in one blaze.
Corner lies on very steep SE slope, approx. 200 ft. NW of mail road up Calapooya (at nearest point)

Fd. Ok by Greg Lang - April 2002 - M139-73
FD. ok by Kris DeGroot, 8/2008 - 2008-0061A-G