

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31 of T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, Contract #152 dated June, 1871
(DCSO records, Volume 9 Page Page 3667)

Set $\frac{1}{4}$ sec. post, from which
 A Fir 18" dia. bears S.80°E., 7 lks. dist.
 A Fir 12" dia. bears S.50°W., 7 lks. dist.

C.E. Roberts - For: J.S. Hunt - May 28, 1903 - Field Book 7
Page 8-9

Reset Post.
 Madrone 10" N.72°W., 10 lks.
 Cedar 48" S.59°E., 31 lks.

Bureau of Land Management Dependent Resurvey - Norman D. Price
Special Instructions dated April 5, 1940 - Survey, 1943
(DCSO records, Volume 27, Page 11520-21)

Point for orig. $\frac{1}{4}$ cor. determined at the record measurements
from both old bearing trees.
At point for corner, set an iron post, 3 ft. long, 1" dia. 28"
in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd:

$\frac{1}{4}$
|
S36|S31
1943

from which

A Fir 30" dia. bears S.70°E., 7 lks. dist. mkd. on bark
 $\frac{1}{4}$ S B T. I re-blaze and re-mark this old bearing
tree $\frac{1}{4}$ S 31 B T.
A Fir stump 14" dia. bears S.45°W., 7 lks. dist. with
only axe marks (old BT)
A Fir 22" dia. bears N.42 $\frac{1}{2}$ °W., 45 lks. dist. mkd. $\frac{1}{4}$
S 36 B T. (New BT)

Found OK, 1958 Dependent Resurvey - Zirpel, Corbin and
Roseberry (DCSO records, Volume 29 Page 12262)

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 9/26/2007 - C.S. File 67/24-27

Found - 2 $\frac{1}{2}$ " dia., brass cap marked as per rec. on 1" O.D.
iron pipe, projects 22" above ground. Base of
iron pipe appears undisturbed.
30" now 25" dia. burnt fir snag, approx 50 ft. tall,
tagged, no marks visible, bears S.70°E., 6.6 ft
to center of root crown, 1943 rec. dist. would
fit well as a face meas. (1943 rec. S.70°E.,
4.6 OBT) continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 31 of T25-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

22" Fir now blow down is tagged - no position;
root hole indeterminate (rec. N.42½°W., 29.7 ft.)
1943 BT

No trace of any other BTs noted.

New - 14" dia., D.Fir double blazed & scribed "¼ S31 CS
BT" bears S.57°E., 30.0 ft.

"X" chiseled into face of sandstone outcrop "X" is
approx. 4" tall bears N.20°W., 7.3 ft.

17" dia., D.Fir, pistol butt, double blazed &
scribed "¼ S36 CS BT" bears S.52½°W., 47.5 ft.

Note - Corner lies in bottom of steep draw with BC/IP in
bed of seasonal drainage. Drains N.70°E., Put
mound of stone around BC/IP
Compass decl. 16¼°E.