

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31 of T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1871
(DCSO records, Volume 9 Page 3666)

Set post cor. to secs. 25, 30, 31 and 36, from which
An Ash 14" dia. bears N.65°E., 60 lks. dist.
A Maple 12" dia. bears S.50°E., 45 lks. dist.
A W.Fir 8" dia. bears S.50°W., 33 lks. dist.
A W.Fir 16" dia. bears N.15°W., 14 lks. dist.

BLM Dependent Resurvey - Norman Price - Special Instructions
dated April, 1940 - Survey, 1943 (DCSO recs, Vol 27 Page 11521)

Set an iron post 3 ft. long 2" dia. 28" in the ground for cor.
of secs. 25, 30, 31 and 36, with brass cap marked:

T25S
R4W|R3W
S25|S30
S36|S31

1943

from which

An I. Cedar 8" dia. bears N.13½°E., 79 lks. dist. mkd.
T 25 S R 3 W S 30 BT.
A Fir 16" dia. bears S.32 3/4°E., 38 lks. dist. marked
T 25 S R 4 W S 36 B T.
An I. Cedar 7" dia. bears S.10½°W., 46 lks. dist. mkd.
T 25 S R 4 W S 25 B T.
A Fir 24" dia. bears N.44½°W., 90 lks. dist. marked
T 25 S R 4 W S 25 B T.

BLM Dependent Resurvey - Corbin; Zirpel & Roseberry - Special
Instructions dated July 8, 1957 & July 15, 1958 - (DCSO
records, Volume 29 Page 12262)

Found BLM 1943 brass cap, from which

A Cedar 10" dia. bears N.13½°E., 79 lks. dist. with
scribe marks T25S R3W S30 BT visible on open blaze.
A Cedar 13" dia. bears S.10½°E., 46 lks. dist. with a
healed blaze.

and new bearing trees:

A Cedar 16" dia bears S.15°E. 161 lks mkd T25S R3W S31 BT
A Cedar 18" dia bears N.7°W., 160 lks mkd T25S R4W S25 BT

FD. by Ken Hoffine, 8/2007 - M154-16

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 9/26/2007 - C.S. File 67/24-20

Both cedar trees from 1958 ren. alive & well.