TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30 of T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W. H. Byars, Contract #152 dated June 1871
(DCSO records, Volume 9 Page 3666)

Set ¼ sec.post from which
A Laurel 12" dia. bears N.45°W., 19 lks. dist.
A Fir 10" dia. bears S.8°E., 34 lks. dist.

Bureau of Land Management Dependent Resurvey - Norman Price
Special Instructions dated April, 1940 - Survey, 1943
(DCSO records, Volume 27 Page 11522)

Point for orig. ¼ sec. cor., determined by reference to the record bearing and distance from the orig. SE BT.
At point for corner, set an iron post 3 ft. long 1" dia. 28" in the ground, with brass cap mkd: ¼
S25|S30
1943 from which
A Fir 18" dia. bears S.8°E., 34 lks. with blaze healed.
I re-blaze and re-mark this old BT ¼ S 30 B T.
A Fir 18" dia. bears N.81½°W., 44 lks. marked ¼ S 25 B T.
(new BT)

Found OK, 1958 BLM Dependent Resurvey - Corbin, Zirpel and Roseberry - (DCSO records, 12262-63)

FD. by Ken Hoffine, 8/2007 - M154-16

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - Kody Inda - 9/11/2007 - C.S. File 67/24-17

Found - 2½" dia., brass cap properly marked on 1" O.D. Iron pipe, firmly set, projects 4" above ground.
Orig. 10" now 19" dia., D.fir stump, 6 ft tall capped w/sheet metal, partly healed single blaze w/scribing "¼" visible bears S.8°E., 22.4 ft. (agrees w/rec.) OBT
18" now 21" dia., D.Fir stump, 5 ft. tall capped w/sheet metal healed single blaze, bears N.81½°W., 29.0 ft. (agrees w/rec) 1943 BT.
New - 12" dia., D.Fir double blazed & scribed "¼ S25 CS BT" bears S.12½°W., 6.6 ft.
14" dia., D.Fir double blazed & scribed "¼ S30 CS BT" bears S.30¾°E., 20.5 ft.
36" dia., I.Cedar double blazed & scribed "¼ S25 CS BT" bears N.3°W., 106.7 ft.

continued next page

TOWNSHIP 25 RANGE 04 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 25; & S30 T25-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Note - 11" dia., D.Fir double blazed & scribed "¼ S30 CS BT" bears N.65½°E., 22.0 ft.
Lies near top of cut bank of overgrown dirt road.
Compass decl. 16¼°E.